



Toor • wall • countertop



UNVEIL UNMISTAKABLE BEAUTY.


CONJURING THE AMBIENCE OF AN ITALIAN PIAZZA, THE BENEFITS OF THIS COLLECTION GO WELL BEYOND THE SURFACE.

REVEAL IMAGING™

UNVEIL THE BEAUTY OF NATURE. To bring the richness of travertine into your installation, Reveal Imaging[™] creates a look that's virtually indistinguishable from natural stone, with the durability and ease of cleaning found in porcelain tile.

MICROBAN® **TECHNOLOGY**

Features Microban **Antimicrobial Protection** for on-going protection against stain- and odorcausing bacteria — great for keeping surfaces cleaner between cleanings.



PTCA

San Michele has been certified by the Porcelain Tile Certification Agency.



RECYCLED MATERIALS

Over 50% pre-consumer recycled materials make San Michele a more environmentally friendly choice for your home or installation, helping minimize your impact on the environment.



Cross-Cut Field Tile



CREMA SI30 (CROSS-CUT)



DORATO SI31 (CROSS-CUT)



MOKA SI32 (CROSS-CUT)

Vein-Cut Field Tile AVAILABLE IN 12 x 24 ONLY.



CREMA SI40 (VEIN-CUT)



DORATO SI41 (VEIN-CUT)



MOKA SI42 (VEIN-CUT)

Mosaics AVAILABLE IN CROSS-CUT ONLY.

Decorative Accents



CREMA SI30 2 x 4 MOSAIC



CREMA DECORATIVE ACCENT SI50



DORATO SI31 2 x 4 MOSAIC



DORATO DECORATIVE ACCENT SIST



MOKA SI32 2 x 4 MOSAIC



MOKA DECORATIVE ACCENT SI52

CREATIVE IDEAS



CREMA SI40 (VEIN-CUT)



DORATO SI41 (VEIN-CUT)



MOKA SI42 (VEIN-CUT)



CREMA SI30 (CROSS-CUT)



DORATO SI31 (CROSS-CUT)



MOKA SI32 (CROSS-CUT)



METAL AGES ROMAN SHIELD MA22 4 x 12 ACCENT STRIP



METAL AGES POLISHED BRONZE MA12 4 x 12 ASHLAR CHAIR RAIL




METAL SIGNATURES AGED BRONZE JARDIN MSI I BORDER

Pattern Ideas



BRICK PATTERN



ALTERNATING VERTICAL



BASKETWEAVE VERTICAL



SIZES

		SQ.FT. CARTON	PIECES PER CARTON
24 x 24 Field Tile	23-1/3" x 23-1/3" (59.48 cm x 59.48 cm)	15.39	4
12 x 24 Field Tile*	11-1/2" x 23-1/3" (29.58 cm x 59.48 cm)	15.40	8
18 x 18 Field Tile	17-1/2" x 17-1/2" (44.53 cm x 44.53 cm)	12.98	6
12 x 12 Field Tile	11-1/2" x 11-1/2" (29.58 cm x 29.58 cm)	11.62	12
2 x 4 Mosaic** (Mesh-mounted on II-I/2" x II-I/2" Sheet)	I-7/8" × 3-7/8" (29.58 cm × 29.58 cm)	8.79	9
2 x 12 Decorative Accent	1.75" x 11-1/2" (4.5 cm x 29.58 cm)		10

^{*}Vein-Cut is only available in 12 x 24. ** Mosaic available in cross-cut only.

RESIDENTIAL USAGE

FLOOR	WALL	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	С	EP	(EX)

Suitable for exterior floors and walls in freezing and non-freezing climates when proper installation methods are followed. Not recommended for pool decks.

COMMERCIAL APPLICATION

	LIGHT COMMERCIAL	COMMERCIAL	COMMERCIAL EXTERIORS
Floors	•	•	
Walls/Backsplashes	•	•	•
Counters	•	•	•
Pool Decking			
Pool Linings	•	•	•

Suitable for exterior walls only in freezing and non-freezing climates when proper installation methods are followed.

TRIM

ТҮРЕ	NUMBER	SIZE	PCS. PER CARTON
Bullnose (Cross-Cut only)	P-43C9	3" × 12"	30

SHADE VARIATION



RANDOM (V4)
Extreme color and texture variation from tile to tile and within each tile; a random look.

INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
3/8"	1/8" (3/16" when rectangular sizes are used in a staggered brick-joint pattern, where the overlap does not exceed 33%)

SLIP RESISTANCE (WET) : 3 The higher the rating, the higher the slip resistance.

I < .50	
2 < .50 .5059	
3 ≥ .60	

TEST RESULTS 🕹

	ASTM#	RESULTS
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Coefficient of Friction (Unpolished)	C1028	Wet: ≥ 0.60 Dry: ≥ 0.65
Abrasion Resistance	C1027	4

NOTES

Use of a latex modified thin-set is recommended for proper installation.

Special care needs to be given when installing tiles 20" and larger. Please refer to www.daltileproducts.com/LargeTiles for information.

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A 1371.1 standards.

For additional information, refer to "Factors to Consider" at www.daltile.com/ CommercialFactors.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.









By their very design, Daltile products can help make it easier for you to earn LEED $^{\!\scriptscriptstyle{\mathrm{M}}}$ points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit daltilegreenworks.com.



 $\label{eq:microban} \begin{tabular}{ll} Microban \begin{tabular}{ll} Antimicrobial Technology is not designed to replace normal cleaning practices or protect users against foodborne illness. MICROBAN is a registered trademark of Microban Products Company. \end{tabular}$













All or selected items within this series are Made in the USA. For more information visit www.daltile.com/c/SanMichele.



