

union square™

floor/wall/countertop
glazed PAVER TILE



Terrace Beige US01



Heirloom Rose US02





Courtyard Red US03



Cobble Brown US04



sizes:

- 
4" x 8" Paver
 (Nominal 3-7/8" x 8")
 (Nominal 9.8 cm x 20.3 cm)
 7/16" thick
 Sq. ft. per carton: 8.0
 Pieces per carton: 36
 - 
2" x 8" Brick
 (Nominal 2-1/4" x 8")
 (Nominal 5.7 cm x 20.3 cm)
 7/16" thick
 Sq. ft. per carton: 6.25
 Pieces per carton: 50
- Grout joint recommendation: 3/8"

approved usage: Floors, Walls, Countertops & Exteriors

F	W	C	E
Floors	Walls	Countertops	Exteriors

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. For additional product information, refer to "Factors to Consider" at www.daltile.com/ResidentialFactors. Not for use on ramps.

shade variation:



Random – Extreme color and texture variation from tile to tile and within each tile; a random look.

durability:

Floor Wear Resistance

1	Residential Bathrooms
2	All Residential Areas
3	All Residential/Light Commercial
4	All Residential/Commercial

slip resistance (wet):

The higher the rating, the higher the slip resistance.

1	<.50
2	.50 - .59
3	≥.60

tile pattern guide


Herringbone



Basketweave



Corridor Horizontal



Brick Weave Vertical



Note: Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim, and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface.

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Use of a latex modified thin-set is recommended for installation.



daltile®

7834 C.F. Hawn Freeway
 Dallas, TX 75217
 214-398-1411. 800-933-TILE

For more information about Daltile products and services, visit our website at daltileproducts.com