

COLORBODY™ PORCELAIN
ALTA VISTA™



 **daltile**[®]
DESIGN WITH CONFIDENCE™



ALTA VISTA™

COLORBODY™ PORCELAIN

floor • wall • countertop

Field Tile



DESERT SAND AV50



SUNSET GOLD AV51



MISTY RAIN AV52



DRIFT WOOD AV53

CREATIVE IDEAS

Color



DESERT SAND AV50



SUNSET GOLD AV51

Accent



FASHION ACCENTS
POSITANO FA98
4 x 13 Travertine Accent Strip



FASHION ACCENTS
CROSSROADS WHITE FA88
3 x 9 Decorative Accent

Color



MISTY RAIN AV52



DRIFT WOOD AV53

Accent



FASHION ACCENTS
WROUGHT IRON GREY FA32
3 x 8 Accent Strip



FASHION ACCENTS
TRIBAL FA87
3 x 12 Decorative Accent

Pattern Ideas



BRICK-JOINT



DIAMOND



HOPSCOTCH

SIZES

		SQ.FT. CARTON	PCS. PER CARTON
18 x 18 Field Tile	(17-3/4" x 17-3/4") (45.2 cm x 45.2 cm)	15.26	7
12 x 12 Field Tile	(11-13/16" x 11-13/16") (30.0 cm x 30.0 cm)	12.59	13

RESIDENTIAL USAGE

FLOORS	WALLS	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	C	EP	ED

COMMERCIAL USAGE

	INTERIOR			EXTERIOR	
	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL	RESIDENTIAL	COMMERCIAL
Floors/Patios	✓	✓	✓	✓	✓
Walls/Backsplashes	✓	✓	✓	✓	✓
Countertops	✓	✓	✓	✓	✓
Pool Decking	✓			✓	
Pool Linings	✓	✓	✓	✓	✓

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

Suitable for exterior patios (excluding pool decks) and walls in freezing and non-freezing climates when proper installation methods are followed.




Use of a latex modified thin-set is recommended for installation. Not for use on ramps.

NOTES

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.


Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

TRIM

	TYPE	NUMBER	SIZE	PCS. PER CARTON
	Bullnose	S-43C9	3 x 12	30
	Cove Base*	S-36C9T	6 x 12	22
	Outcorner	SC-36C9T	1 x 6	15

* Cove Base trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

SHADE VARIATION



INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
1/4"	3/16"

DYNAMIC C.O.F. (WET) : 2

The higher the rating, the higher the slip resistance.

1 < .42

2 ≥ .42

STATIC C.O.F. (WET) : 3

1 < .50

2 .50 - .59

3 ≥ .60

TEST RESULTS

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	275 lbs
Scratch Hardness	MOHS	8.5
Chemical Resistance	C650	Resistant
Dynamic C.O.F.	A137.1	≥ 0.42
Static C.O.F.	CI028	Wet: ≥ 0.60 Dry: ≥ 0.79

Dynamic C.O.F. (Wet) value as measured by the DCOF AcuTest™ helps to assess a products suitability for a commercial environment. For more information, visit our website at www.daltile.com/DCOF.



daltile
greenworks™
ENVIRONMENTAL LEADERSHIP THAT WORKS

By their very design, Daltile products can help make it easier for you to earn LEED™ points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit daltilegreenworks.com.



All or selected items within this series are made in the USA. For more information visit www.daltile.com/AltaVista



7834 C. F. Hawn Freeway | Dallas, TX 75217 | 214.398.1411 800.933.TILE
For more information about Daltile products and services, visit our website at daltile.com