



Campione

Exhibiting the true heart of a champion, Campione takes travertine-inspired tile to a whole new level.

The smooth surface belies the three-dimensional impression of crater-like depressions and lava-like flow that bring a dramatic feeling of movement to this glazed porcelain series.

The large-scale field tile plus three modular iterations bring warmth and presence to areas of congregation, whether public or private. Three rich, neutral colors are beautiful in a great room; blissful on a spa wall; welcoming in a hospitality lobby. Plus, the simple maintenance routine requires no harsh chemicals or repeated cycles of sealing and stripping as does natural travertine.



Tile shown Andretti Mosaic - Octagon 2"x2"





An octagon-shaped mosaic for each color, with stone dots, adds pattern contrast to the square and rectangular shapes. Or opt for metal or glass accessories to customize this revitalized classic into a champion look of your own.



Campione floor and wall tile - glazed porcelain stoneware







UHAN Andretti 13"x13"



UHAT Armstrong 20"x20"



UHAP Armstrong 13"x13"



UHAU Sampras 20"x20"



UHAQ Sampras 13"x13"





Decorative Options





UJ63 Bronze UJ65 Bronze UJ67 Bronze Insert 1"x1"

UJ28 Andretti



UJ3B Andretti 3¼"x6½"



UHA6 Andretti Mosaic - Octagon 2"x2" 13"x13"



UJ29 Armstrong 6½"x6½"



UJ3C Armstrong 3¼"x6½"



UHA7 Armstrong Mosaic - Octagon 2"x2" 13"x13"



UJ3A Sampras 6½"x6½"





UHA8 Sampras Mosaic - Octagon 2"x2" 13"x13"



Crystal Stone LG4J Gold 12"x12"



Crystal Stone LG4E Coffee 12"x12"

Trims



UHA2 Andretti Bullnose 3"x13"

ASTM Test Results

Water Absorption

Scratch Resistance

Breaking Strength

Facial Dimension

Wedging (squareness) Warpage (flatness)

Dry Coefficient of Friction

Wet Coefficient of Friction

Chemical Resistance

Thickness

Class (PEI)

Frost Resistance

Technical Characteristics



ASTM Test Results

≤ 0.50%

≥ 418 lbs. (190 kg)

Within Standard

Within Standard

Within Standard

Within Standard

Class IV*

0.70 ≤ C.O.F. < 0.80

0.60 ≤ C.O.F. < 0.70

Class A

Class A

Chair Rail 2"x13"

ASTM Standards

≤0.50%

As Reported

MOHS 1-10

≥ 250 lbf.

-3.0% < Nominal ≤ 3.0%

≤ 0.04 in (1.02 mm max)

+/- 0.50% or +/- 2.0mm**

+/- 0.75% or +/- 2.3mm**

Class 0 - Class V

As Reported

As Reported

Class A - Class E



Field Tile

Wall Tile

0.6 C.O.F. (Wet)

0.7 C.O.F. (Dry)

Modular Tile

Abrasion Resistance

UHA3 Armstrong Bullnose 3"x13"

ASTM Test Methods

C373

MOHS Scale

C648

C499

C499

C502

C485

C1027

C1028

C1028

C650

C1378



UJ6P Bronze Chair Rail 2"x13"

Decorative Tile

V2 Slight Variation

Trim Available

Frost Resistant

Spec Wizard

Meets ADA Recommendations

UHA4 Sampras Bullnose 3"x13"

UJ6N Nickel Chair Rail 2"x13"

UJ6P Bronze Chair Rail 2"x13"

HAMAZER	Sizes	Pcs	Sq. Ft.	Weight (lbs.)	Thickness
Modular Tile	3¼"x 6½"	72	10.55	42	0.334
Modular Tile	6½"x 6½"	36	10.55	42	0.334
Modular Tile	13"x 13"	15	17.91	67	0.334
Field Tile	20"x 20"	6	16.15	84	0.433
Mosaic - Octagon 2"x2"	13"x 13"	10		39	Compatible
Insert	4"x 4"	15		7	Compatible
Insert	2"x 2"	60		13	Compatible
Insert	1"x 1"	125		14	Compatible
Crystal Stone	12"x 12"	12	11.63	42	Compatible
Chair Rail	2"x 13"	20		5	Compatible
Bullnose	3"x 13"	20		21	Compatible

	Sizes	Ctn	Sq. Ft.	Weight (lbs.)
Modular Tile	3¼"x 6½"	51	538.05	2142
Modular Tile	6½"x 6½"	51	538.05	2142
Modular Tile	13"x 13"	38	680.58	2546
Field Tile	20"x 20"	24	387.60	2016



Stain Resistance Class A - Class E

^{*} Durability Classification / Suggested Applications Class IV Moderate / Heavy traffic: Tile suggested for residential, medium commercial and light institutional floor and wall applications ** Which ever is less



CAMPIONE is available nationwide. To locate your nearest Distributor call American Marazzi Tile Customer Service or visit www.marazzitile.com

DISTRIBUTED BY:

American Marazzi Tile, Inc. Headquarters & Manufacturing Plant Telephone 972.226.0110

972.226.5629

359 Clay Road Sunnyvale, Texas 75182 www.marazzitile.com contact@marazzitile.com

Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with American Marazzi Tile Customer Service for details.