



POZZALO™

GLAZED CERAMIC WITH REVEAL IMAGING™

FLOOR & WALL



AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

POZZALO™

Let the earthy tones of Pozzalo™ glazed ceramic tile envelop you with a sense of radiating warmth. With Pozzalo™, you'll capture the classic ambience of a distant travertine courtyard, anywhere you desire.

- Travertine look
- Available in four colors
- Ideal for floors and walls

Photo features Coastal Beige 9 x 12 and Universal 2 x 2 Mosaic on the wall

FIELD TILE



SAIL WHITE PZ91



COASTAL BEIGE PZ92



WEATHERED NOCE PZ93



MANOR GRAY PZ94

WALL TILE



SAIL WHITE PZ91



COASTAL BEIGE PZ92



WEATHERED NOCE PZ93



MANOR GRAY PZ94

COORDINATING MOSAIC TILE



UNIVERSAL PZ99
2 x 2 Mosaic
Features: Sail White, Coastal Beige, Weathered Noce and Manor Gray

DECORATIVE TILE



UNIVERSAL PZ99
2 x 9 Wall Accent
Features: Sail White, Coastal Beige, Weathered Noce and Manor Gray

SIZES, SHADE VARIATION & PRICING



18 x 18 FIELD TILE
(17-3/4" x 17-3/4")
(45.20 cm x 45.20 cm)



12 x 12 FIELD TILE
(11-13/16" x 11-13/16")
(30.00 cm x 30.00 cm)




9 x 12 WALL TILE
(9" x 12")
(22.91 cm x 30.54 cm)



6 x 6 WALL TILE
(6" x 6")
(15.31 cm x 15.31 cm)



2 x 9 WALL ACCENT
(1-13/16" x 9")
(4.60 cm x 22.90 cm)



2 x 2 MOSAIC
(Dot-mounted)
(12" x 24" Sheet)
(30.48 cm x 60.96 cm Sheet)



HIGH
(V3)



MOSAIC
RANDOM
(V4)

TILE THICKNESS:
5/16" Floor & Wall, 1/4" Mosaic
RECOMMENDED
GROUT JOINT:
3/16" Floor, 1/16" Wall
& 1/8" Mosaic
RELATIVE PRICING: Low

TRIM



FLOOR BULLNOSE +
P-43C9
3 x 12



WALL BULLNOSE
S-4309 (9" side)
3 x 9



WALL BULLNOSE OUTCORNER
SN-4309
3 x 3



WALL SURFACE BULLNOSE
S-4669
6 x 6



WALL BULLNOSE OUTCORNER
SCRL-4669
6 x 6



RADIUS BULLNOSE
A-4200
2 x 6



RADIUS BULLNOSE OUTCORNER
AN-4200
2 x 2



WALL BULLNOSE
S-4269 (6" side)
2 x 6



WALL BULLNOSE OUTCORNER
SN-4269
2 x 2



MOSAIC BULLNOSE
S-886
2 x 2



COUNTER RAIL
26-CRWL
2 x 6



COUNTER RAIL CORNER
22-CRCN
2 x 2




QUARTER ROUND
A-106
1 x 6




QUARTER ROUND OUTCORNER
UC-106
1 x 1

+ Floor bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.


PATTERN IDEAS



DIAMOND PATTERN
100 pcs. per 100 s/f
12 x 12 100%



GRID PATTERN
100 pcs. per 100 s/f
12 x 12 100%



BRICK PATTERN
100 pcs. per 100 s/f
12 x 12 100%
OR
400 pcs. per 100 s/f
6 x 6 100%

PERFORMANCE CHARACTERISTICS

	MOISTURE ABSORPTION	BREAKING STRENGTH	MOHS	CHEMICAL RESISTANCE	ABRASION RESISTANCE
Floor	< 7.0%	> 250 lbs.	8.0	Resistant	4
Wall	< 20.0%	120 - 230 lbs.	4.0 - 6.0	Resistant	N/A
Mosaic	< 3.0%	> 250 lbs.	8.0	Resistant	4

CLEANING PROCEDURES

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

INSTALLATION METHODS BACKING MATERIALS

- Concrete
- Exterior grade plywood
- Cementitious backer board

SETTING

- Latex modified thin-set
- Epoxy

GROUTING

- Sanded grout / Unsanded grout for wall
- Sanded cement grout / Unsanded cement grout for wall
- Epoxy grout

FLOOR APPLICATIONS

(EXCLUDES WALL TILE)	TARGET DCOF WET	SUITABLE
Dry & Level - Interior	N/A	●
Wet & Level - Interior	≥ 0.42	●
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	○
Ramps & Inclines	≥ 0.65	○

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit www.americanolean.com/dcof.

OTHER APPLICATIONS

	SUITABLE
Walls/Backsplashes	●
Countertops	●**
Pool Linings	●*

APPLICATION NOTES:

** Does not apply to 9 x 12 wall tile.

* Mosaic & 6 x 6 wall tile only.

Suitable for exterior applications in non-freezing climates only when proper installation methods are followed.

NOTES

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.

Wall accent suitable for wall applications only.

For additional information, refer to "Factors to Consider" at <http://americanolean.com/factors-to-consider.cfm>.



POST-CONSUMER RECYCLED MATERIALS



PRE-CONSUMER RECYCLED MATERIALS



REVEAL IMAGING