

E L E M E N T A L N A T U R A L S

Amber Valley™



Porcelain Tile



Amber Valley™

Features

- Emulates look of natural slate
- Modular for pattern layouts
- Warm color variations
- Coordinates with Tumbled Slate

Field Tile



Millstone Beige AM85



Derby Brown AM89



Bowling Green AM88



River Moss AM87

Mosaic Tile



Millstone Beige AM85
Mosaic
3" x 3"



Derby Brown AM89
Mosaic
3" x 3"



Bowling Green AM88
Mosaic
3" x 3"



River Moss AM87
Mosaic
3" x 3"

COORDINATING DECORATIVE TILE SUGGESTIONS



India Autumn/India Multicolor TU79
Stepping Stone Border 3" x 12"
Coordinates with AM85, AM88, AM89



India Autumn/India Multicolor TU78
Geometric Border 3" x 12"
Coordinates with AM87, AM88, AM89



China Gold/China Multicolor TU76
Geometric Border 3" x 12"
Coordinates with AM85, AM88, AM89




China Gold/China Multicolor TU77 Mosaic
Serpentine Border 4" x 12"
Coordinates with AM85 and AM89

COORDINATING TILE SUGGESTIONS



Tumbled Slate
India Autumn TU73



Candalara Glass
English Ivy CL52




Tumbled Slate
India Multicolor TU72



Saxon Metals
Bronze SX91

SIZES



20" x 20" Field Tile
(19 3/4" x 19 3/4" nominal)
(50.2 cm x 50.2 cm nominal)




13" x 13" Field Tile
(13 1/8" x 13 1/8" nominal)
(33.3 cm x 33.3 cm nominal)



6 1/2" x 6 1/2" Field Tile
(6 7/16" x 6 7/16" nominal)
(16.4 cm x 16.4 cm nominal)

Tile Thickness: 5/16"
Recommended grout joint: 3/16"

Shade Variation: Random (V4)




3" x 3" Mosaic Tile (mesh-mounted)
(13 1/8" x 13 1/8" sheet nominal)
(33.3 cm x 33.3 cm sheet nominal)


TRIM



Bullnose
P43E9 3" x 13"



Bullnose
P4669 6 1/2" x 6 1/2"



Cove Base
S36E9TB 6" x 13 1/8"



Cove Base Outcorner
SC36E9TB 1" x 6"

Information

Applications

	Residential	Light Commercial	Commercial
Floors†	X	X	X
Walls	X	X	X
Countertops	X	X	X
Backsplashes	X	X	X

† Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. For additional information, refer to "Factors to Consider" at www.americanolean.com/ResidentialFactors

- Suitable for exterior floors, walls and patios (excluding pool decks) in freezing and non-freezing climates when proper installation methods are followed
- Special Installation Requirement: for proper bonding, medium bed mortar should be utilized in installing tiles with a dimensional length size greater than 20" x 20", large rectangles or tiles with greater dimensional thickness than normal. Back buttering tiles of this nature in the installation process will also assure proper coverage for bonding.
- Use of a latex modified thin-set is recommended for proper installation.

Price Structure

Premium

Preferred

Stylish and elegant looks. Each tile is created through traditional firing processes and glaze techniques.

Premium

Sophisticated visuals and detailed surfacing. A process of multiple glazes results in an attractive, cultured surface.

Premier

Inherent visual color and depth. A complex process of design brings out the rich, more upscale texture and look of elegant porcelain as well as a variety of other tiles.

Prestige

Natural characteristics and realistic attributes. Captures the inherent beauty of natural stone. Highly complex design techniques are also applied to rich porcelains, unique glasses and other materials to create surfaces with distinctive physical and natural qualities.

Performance characteristics


C.O.F.		Moisture Absorption	Breaking Strength	MOH's	Chemical Resistance
Wet	Dry				
≥0.60	≥0.70	<0.5%	>300 lbs.	8.0	AM85 = 4 AM87, AM88, AM89 = 3

Abrasion Resistance Application Classifications ISO 10545-7

1 Light Residential
2 Heavy Residential


3 Light Commercial
4 Heavy Commercial

Patterns



Hopscotch Pattern

67 pcs. 13" x 13" 80%
69 pcs. 6 1/2" x 6 1/2" 20%



Modified Hopscotch Pattern

24 pcs. 20" x 20" 65%
24 pcs. 13" x 13" 28%
24 pcs. 6 1/2" x 6 1/2" 7%

* Dark lines indicate repeat

Cleaning Procedures

- Remove loose dust and dirt with a damp cloth or a sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

Special Notes

Special installation requirement: For proper bonding, medium bed mortar should be utilized in installing tiles with a dimensional length size greater than 20" x 20", large rectangles or tiles with a greater dimensional thickness than normal. Back buttering tiles of this nature in the installation process will also assure proper coverage for bonding.

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions.

Use of a latex modified thinset is recommended for installation.