



pozzalo™

GLAZED CERAMIC TILE





GLAZED CERAMIC TILE

pozzalo™

Let the earthy tones of Pozzalo glazed ceramic tile envelop you with a sense of radiating warmth.

With Pozzalo, you'll capture the classic ambience of a distant travertine courtyard, anyplace you desire.

- Travertine look
- Available in five colors
- Ideal for floors and walls alike

FIELD TILE



Sail White PZ91



Coastal Beige PZ92



Weathered Noce PZ93



Manor Gray PZ94

MOSAIC TILE




Universal Mosaic Blend PZ99

DECORATIVE ACCENTS



Universal PZ99

SIZES, SHADE VARIATION & PRICING



18 x 18 Floor Tile
(17 7/8" x 17 7/8")
(45.2 cm x 45.2 cm)




12 x 12 Floor Tile
(11 13/16" x 11 13/16")
(30 cm x 30 cm)



9 x 12 Wall Tile
(8 15/16" x 11 15/16")
(22.7 cm x 30.3 cm)



6 x 6 Wall Tile
(6" x 6")
(15.2 cm x 15.2 cm)



2 x 2 Mosaic Tile
(2" x 2")
(12" x 24" sheet)
(30.48 cm x 60.96 cm sheet)



High
(V3)

Tile Thickness: 5/16" Wall & Floor, 1/4" Mosaics
Recommended Grout Joint: 3/16" Floor, 1/8" Mosaics, 1/16" Wall
Relative Pricing: Low

TRIM



Floor Bullnose
P43C9 3 x 12



Bullnose
S4309 3 x 9



Bullnose Corner
SN4309 3 x 3



Quarter Round
A106 1 x 6



Quarter Round Corner
UC106 1 x 1



Surface Bullnose
S4269 2 x 6




Surface Bullnose Outcorner
SN4269 2 x 2



Bullnose
S4669 6 x 6



Bullnose Corner
SCRL4669 6 x 6



Radius Bullnose
A4200 2 x 6



Radius Bullnose Outcorner
AN4200 2 x 2



Counter Rail
26CRWL 2 x 6




Counter Rail Corner
22CRCN 2 x 2




Mosaic Bullnose
S886MS 2 x 2




PATTERN IDEAS



Diamond Pattern
100 pcs. per 100 s/f
12 x 12 100%



Grid Pattern
100 pcs. per 100 s/f
12 x 12 100%



Brick Pattern
100 pcs. per 100 s/f
12 x 12 100%
OR
400 pcs. per 100 s/f
6 x 6 100%

PERFORMANCE CHARACTERISTICS

	C.O.F.		Moisture Absorption	Breaking Strength	MOH's	Abrasion Resistance	Chemical Resistance
	Wet	Dry					
FLOOR	≥0.60	≥0.65	<3%	>250 lbs.	8.0	4	Resistant
WALL	≥0.50	≥0.80	<20%	100-230 lbs.	4.0-6.5	N/A	Resistant
MOSAICS	≥0.60	≥0.65	<3%	>250 lbs.	8.0	N/A	Resistant

Cleaning Procedures

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

Installation Methods

Backing Materials

- Concrete
- Mortar bed
- Cementitious backer board

Setting

- Latex modified thin-set
- Epoxy

Grouting

- Sanded grout
- Recommended grout joint: 3/16" Floor, 1/8" Mosaics and 1/16" Wall

NOTES

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.



POST CONSUMER
RECYCLED MATERIALS



PRE CONSUMER
RECYCLED MATERIALS



American Olean Greenworks is part of the Mohawk Greenworks™ corporate initiative. Visit mohawkgreenworks.com for more details.

APPLICATION

FLOOR & MOSAICS

RES	LT COM	HVY COM	EXT	
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	Floors †
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	Walls/Backsplashes
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	Countertops
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	Pool Decking
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	Pool Lining

WALL

RES	LT COM	HVY COM	EXT	
<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	Floors †
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	Walls/Backsplashes
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	Countertops
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	Pool Decking
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	Pool Lining

APPLICATION NOTES:

† Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Suitable for exterior walls only in non-freezing climates when proper installation methods are followed.

Floor field tile suitable for pool linings in non-freezing climates only.

Not for use on ramps.

For additional information, refer to Factors to Consider at www.americanolean.com/CommercialFactors.