TECHNICAL DATASHEET

-Hudson Reed_

Kubix Twin Concealed Thermostatic Shower Valve

Barcode	5055146131472
Product Code	A3013
Finishes	Chrome
Product Type	Thermostatic Shower Valve
Water Pressure	LP1 - 0.1 bar pressure minimum
Standards	BC254/0207, EN200 and/or WRc/NSF
Requirement	Suitable for all plumbing systems

Guarantee & Aftercare

During installation extra care must be taken to avoid damaging the fittings. We provide a 20 year guarantee against faulty workmanship or materials (excluding serviceable parts), providing they have been installed, cared for and used in accordance with our instructions.



ADDITIONAL INFORMATION


- Can be fitted vertically or horizontally
- TMV2 Approved


Bar	Flow I/min
0.1	5.5
0.5	14
1	20
2	29
3	44

COMPLIANCE: Pending

CUSTOMER CARE:

For further information please call 01282 446789





KEY TO PRODUCT PRESSURE REQUIREMENTS	

I D 0.1 bormin I D 0.0 bormin MD 0.5 bormin UD1 1 bormin	UD9 9 hormin
LP - 0.1 bar min LP2 - 0.2 bar min MP - 0.5 bar min HP1 - 1 bar min	ПГ 2 - 2 Vai IIIII

Ultra Finishing Ltd, Widow Hill Road, Heasand ford Industrial Estate, Burnley, Lancashire, BB10 2BQ Telephone: 01282 436934 Fax: 01282 428915 Web site: www.homeofultra.com