


VP-25 Visual Presenter



Equipped with a professional grade 2MP CMOS sensor and 9X optical zoom lens, the VP-25 delivers crisp clear images of documents, 3D objects, transparencies, film negatives, microscopic slides and more. Powerful imaging features including freeze frame, mirror, positive/negative, text mode and image rotation empower users to get the best image quality possible for their presentations. The VP-25 also includes a built-in memory for up to 16 images.

Connect to the latest PC and Mac computers using the USB2.0 port, no drivers needed! The VP-25 is plug-and-play with PCs running Windows XP, Vista or Windows 7 as well as Mac OSX (latest version updates strongly reccomended). USB capture software is included for PC users, Mac users can use any USB Webcam compatible software such as iChat.

- Folding Design
- 2MP Image Sensor
- 9X Optical Zoom
- XGA Output
- Full Image Control
- LED Arm Lighting







550 Huyler St • South Hackensack, NJ 07606 800-631-0868 • sales@buhl-ind.com

www.buhl-ind.com



VP-25 Visual Presenter

Product Specifications

Sensor 1/3" CMOS Total pixel 2 Megapixel Zoom 9x optical, 8x digital Frame rate 15 Shooting area Max: 13.5"x10.6", Min: 0.1"x0.1" Focus Auto/manual Output signal XGA Resolution (Horizontal) 650 TV lines Image mirror Yes Image capture Yes, 12 images OSD Yes White balance Auto/manual Image split Yes Color adjustment Yes Brightness adjustment Yes Imput Connections VGA x1 VIDEO x1 Output Connections VGA x1 VIDEO x1 AUDIO x1 S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) Light source Embedded LED arm lamp Dimensions Folded: 12.6"x8.6"x3.7" Setup:19.7"x6.6"x19.3" Power supply 12V DC power adapter Weight(net) Vsa Auto/manual Au	Model	VP-25
Total pixel Zoom 9x optical, 8x digital Frame rate 15 Shooting area Max: 13.5"x10.6", Min: 0.1"x0.1" Focus Auto/manual Output signal XGA Resolution (Horizontal) Image mirror Yes Image capture Yes, 12 images OSD Yes White balance Auto/manual Image split Yes Color adjustment Yes Brightness adjustment Yes Image freeze Input Connections VGA VIDEO x1 Output Connections VGA VIDEO x1 AUDIO x1 S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"x6.6"x3.7" Setup:19.7"x6.6"x19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg		+
Zoom 9x optical, 8x digital Frame rate 15 Shooting area Max: 13.5"x10.6", Min: 0.1"x0.1" Focus Auto/manual Output signal XGA Resolution (Horizontal) 650 TV lines Image mirror Yes Image capture Yes, 12 images OSD Yes White balance Auto/manual Image split Yes Color adjustment Yes Brightness adjustment Yes Image freeze Yes Input Connections VGA x1 VIDEO x1 AUDIO x1 AUDIO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) Light source Embedded LED arm lamp Dimensions Pover supply 12V DC power adapter Weight(net) VGA, SAGA (SI) VIDEO puter Copwer audion of the signal of the supplies of the signal of the signal of the supplies of the signal of		+
Frame rate Shooting area Max: 13.5"x10.6", Min: 0.1"x0.1" Focus Auto/manual Output signal Resolution (Horizontal) Image mirror Yes Image capture OSD Yes White balance Auto/manual Image split Yes Color adjustment Yes Brightness adjustment Yes Input Connections VGA VIDEO Auto/manual V1 V1 V1 V2 V2 V3 V4 V5 V5 V6 V5 V6 V6 V6 V7 V8 V8 V8 V8 V8 V8 V8 V8 V8		
Shooting area Max: 13.5"x10.6", Min: 0.1"x0.1" Focus Auto/manual Output signal XGA Resolution (Horizontal) 650 TV lines Image mirror Yes Image capture Yes, 12 images OSD Yes White balance Auto/manual Image split Yes Color adjustment Yes Brightness adjustment Yes Image freeze Yes Input Connections VGA x1 VIDEO x1 Output Connections VGA x1 VIDEO x1 AUDIO x1 S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) Light source Embedded LED arm lamp Dimensions Folded: 12.6"x6.6"x3.7" Setup: 19.7"x6.6"x19.3" Power supply 12V DC power adapter Weight(net) Folded: 12.5"s6.6"x19.3"		
Focus Auto/manual Output signal XGA Resolution (Horizontal) 650 TV lines Image mirror Yes Image capture Yes, 12 images OSD Yes White balance Auto/manual Image split Yes Color adjustment Yes Brightness adjustment Yes Image freeze Yes Input Connections VGA X1 VIDEO X1 Output Connections VGA X1 VIDEO X1 AUDIO X1 S-VIDEO X1 Computer Connections USB2.0 X1 (USB Camera) REMOTE CONTROLLED AT IMADE Dimensions Folded: 12.6" x6.6" x3.7" Setup:19.7" x6.6" x19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg		+
Output signal Resolution (Horizontal) Image mirror Image capture OSD Ves White balance Image split Color adjustment Brightness adjustment Image freeze Input Connections VGA VIDEO AUDIO AUDIO S-VIDEO Computer Connections USB2.0 RS232 (computer controllable) Light source Dimensions Power supply Poss Pyes Image Split Ves Ruto/manual Ruto/m	Shooting area	
Resolution (Horizontal) Image mirror Image capture OSD Yes White balance Muto/manual Image split Yes Color adjustment Brightness adjustment Image freeze Imput Connections VGA VIDEO VIDEO X1 AUDIO S-VIDEO X1 Computer Connections USB2.0 Remote control Light source Dimensions Folded:12.6"x6.6"x3.7" Setup:19.7"x6.6"x19.3" Power supply Weight(net) Fes Suto/Mosc Ves Sunday Ves Auto/manual Ves Ves Image freeze Yes Image freeze Yes Image freeze Yes Image freeze Yes Image freeze Input Connections VGA X1 VIDEO X1	Focus	Auto/manual
Image mirrorYesImage captureYes, 12 imagesOSDYesWhite balanceAuto/manualImage splitYesColor adjustmentYesBrightness adjustmentYesImage freezeYesImput ConnectionsYGAVIDEOx1Output ConnectionsX1VGAx1VIDEOx1AUDIOx1S-VIDEOx1Computer ConnectionsX1USB2.0x1 (USB Camera)RS232 (computer controllable)x1Remote controlYes(360°controllable)Light sourceEmbedded LED arm lampDimensionsFolded:12.6"x6.6"x19.3"Power supply12V DC power adapterWeight(net)5.5lbs/2.5kg	Output signal	XGA
Image capture Yes, 12 images OSD Yes White balance Auto/manual Image split Yes Color adjustment Yes Brightness adjustment Yes Image freeze Yes Input Connections VGA X1 VIDEO X1 Output Connections VGA X1 VIDEO X1 Computer Connections USB2.0 X1 (USB Camera) Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Power supply 12V DC power adapter Weight(net) Ves	Resolution (Horizontal)	650 TV lines
White balance White balance White balance Image split Yes Color adjustment Yes Brightness adjustment Image freeze Image freeze Input Connections VGA VIDEO X1 Output Connections VGA X1 VIDEO X1 AUDIO X1 S-VIDEO X1 Computer Connections USB2.0 RS232 (computer controllable) Light source Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) Ves	Image mirror	Yes
White balance Image split Yes Color adjustment Yes Brightness adjustment Yes Image freeze Yes Input Connections VGA X1 VIDEO X1 Output Connections VGA X1 VIDEO X1 AUDIO X1 S-VIDEO X1 Computer Connections USB2.0 RS232 (computer controllable) Light source Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply Weight(net) Audio Auto/manual Auto/m	Image capture	Yes, 12 images
Image split Color adjustment Pes Brightness adjustment Image freeze Imput Connections VGA VIDEO VGA VIDEO VGA VIDEO X1 VIDEO X1 VIDEO X1 VIDEO X1 VIDEO X1 VIDEO X1 AUDIO S-VIDEO X1 Computer Connections USB2.0 RE322 (computer controllable) Remote control Light source Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) Ves	OSD	Yes
Color adjustment Brightness adjustment Yes Image freeze Yes Input Connections VGA VIDEO X1 Output Connections VGA X1 VIDEO X1 AUDIO S-VIDEO X1 Computer Connections USB2.0 RE3232 (computer controllable) Remote control Light source Dimensions Power supply Yes Yes Yes Yes X1 X1 X1 X1 X1 X1 X1 X1 X1 X	White balance	Auto/manual
Brightness adjustment Image freeze Input Connections VGA VIDEO X1 Output Connections VGA X1 VIDEO X1 VIDEO X1 AUDIO X1 S-VIDEO X1 Computer Connections USB2.0 RS232 (computer controllable) Light source Dimensions Power supply Tyes Yes Yes Yes X1 X1 X1 X1 X1 X1 X1 X1 X1 X	Image split	Yes
Image freeze Input Connections VGA VIDEO VGA X1 Output Connections VGA X1 VIDEO X1 AUDIO S-VIDEO X1 Computer Connections USB2.0 RE323 (computer controllable) Remote control Light source Dimensions Power supply Testing 12V DC power adapter Weight(net) VIDEO X1 X1 X1 X1 X1 X1 X1 X1 X1 X	Color adjustment	Yes
Input Connections VGA	Brightness adjustment	Yes
VGA x1 VIDEO x1 Output Connections VGA x1 VIDEO x1 AUDIO x1 S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"x6.6"x3.7" Setup:19.7"x6.6"x19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	Image freeze	Yes
VIDEO x1 Output Connections VGA x1 VIDEO x1 AUDIO x1 S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	Input Connections	
Output Connections VGA x1 VIDEO x1 AUDIO x1 S-VIDEO x1 Computer Connections VSB2.0 USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	VGA	x1
VGA x1 VIDEO x1 AUDIO x1 S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	VIDEO	x1
VIDEO x1 AUDIO x1 S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	Output Connections	
AUDIO x1 S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	VGA	x1
S-VIDEO x1 Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	VIDEO	x1
Computer Connections USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	AUDIO	x1
USB2.0 x1 (USB Camera) RS232 (computer controllable) x1 Remote control Yes(360°controllable) Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	S-VIDEO	x1
RS232 (computer controllable) Remote control Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	Computer Connections	
Remote control Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	USB2.0	x1 (USB Camera)
Light source Embedded LED arm lamp Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	RS232 (computer controllable)	x1
Dimensions Folded:12.6"×6.6"×3.7" Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	Remote control	Yes(360°controllable)
Setup:19.7"×6.6"×19.3" Power supply 12V DC power adapter Weight(net) 5.5lbs/2.5kg	Light source	Embedded LED arm lamp
Weight(net) 5.5lbs/2.5kg	Dimensions	
	Power supply	12V DC power adapter
Warranty	Weight(net)	5.5lbs/2.5kg
wallality [5 leafs	Warranty	3 Years







550 Huyler St • South Hackensack, NJ 07606 800-631-0868 • sales@buhl-ind.com

www.buhl-ind.com

