

MD-1524 & MS-1524 Specifications

Finish: All steel components shall be thoroughly cleaned and phosphatized for rust resistance in a five-stage pre-treatment process. A high grade of polyester/epoxy powder paint is to be applied electrostatically with a gloss reading of between 55 and 65. The finish shall have a salt spray rating of 250 hours or more.

MS-1524:

<u>Part Name</u>	<u>Gauge</u>
Door Latch Cam	14
Mod. Door	20
Mod. Door Stiffener	24
Mod. Body Wrap	20
Mod. Back	24
Mod. Corner Angle	16
Mod. Bottom Front Panel	22
Mod. 15" Shelf	20
Mod. Door Frame Stiffener	16
24" Mod. Bottom	24

MD-1524:

<u>Part Name</u>	<u>Gauge</u>
Drawer Divider	22
Drawer Body	24
Drawer Back	24
Drawer Runner	18
Drawer Front	22
Mod. Drawer Stiffener	24
Mod. Body Wrap	20
Mod. Back	24
Drawer Upright	18
Drawer Lock Bar	14
Mod. Drawer Cabinet Bottom Front Panel	22
Mod. Bottom	24
Mod. Drawer Spacer	20
Mod. Drawer Track	18
Mod. Mounting Angle	16