

HEAT CANNON

INDIRECT FIRED HEATERS

Dependable

Heat

Wherever

You Need It



FVO-400



FVP-400

- Indirect fired – heat exchanger allows external exhaust of combustion products
- Thermostatically controlled
- Standard steel lifting harness
- Heavy duty pneumatic tires and slim design provides for easy site mobility and transportation
- FVO-400 model has built-in fuel tank
- Your choice of heating oil, diesel, kerosene propane or natural gas



HEAT CANNON

INDIRECT FIRED HEATERS

OIL, NATURAL GAS, PROPANE



FEATURES

Model:	FVO-400 Oil	FVN-400 Natural Gas	FVP-400 Propane
Heat Capacity	395,000 BTUs	395,000 BTUs	395,000 BTUs
Fuel Tank Capacity	48 US gallons	External n/a	External n/a
Operating Time/ Fuel consumption	16 hours	380 cfm	18.5 lbs/hr
Dimensions	70 inches long, 24 inches wide 52 inches high	70 inches long, 24 inches wide 47 inches high	70 inches long, 24 inches wide 47 inches high
Heat Exchanger	16 gauge 304 Stainless Steel	16 gauge 304 Stainless Steel	16 gauge 304 Stainless Steel
Fan Motor	1 HP@1725 rpm 2500 cfm	1 HP@1725 rpm 2500 cfm	1 HP@1725 rpm 2500 cfm
Ignition	Direct spark ignition	Direct spark ignition	Direct spark ignition
Nozzle Size/Gas Pressure	2.25 U.S. GPH @ 170 PSI	2.0" W.C.	3.2" W.C.
Air Outlet	Two 12 inch diameter	Two 12 inch diameter	Two 12 inch diameter
Wheels	Two 16 inch pneumatic wheels	Two 16 inch pneumatic wheels	Two 16 inch pneumatic wheels
Power Supply	120 Volts, 15 Amps	120 Volts, 15 Amps	120 Volts, 15 Amps
Approvals	cWHus, ETL	cWHus, ETL	cWHus, ETL

OPTIONS



12 inch X 12 ft Flexible Ducting



Remote Thermostat Control
c/w 25 ft Cord



6 Seapark Drive,
St. Catharines, Ontario Canada L2M 6S6
Tel: 905-685-4243 Fax: 905-685-0113
E-mail: flagro@flagro.on.ca Website: www.flagro.on.ca