

LOW-VOLTAGE HEADS

John Head 

DESCRIPTION

Adjustable head tilts and rotates infinitely. Integral louver lens holder can hold a single glass lens (sold separately) or an eggcrate louver (included). Low-voltage, MR16 lamp of up to 50 watts (not included). Works with SORAA.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

ACCESSORIES & OPTICAL CONTROLS

Colored Lens, Dichroic Lens, Diffuser Lens, Eggcrate Louver, Linear Spread Lens, Soft Focus Lens, UV Filter

WEIGHT

0.2lb / 0.09kg ±



satin nickel

straight

with eggcrate louver

ORDERING INFORMATION

700 SYSTEM	JON	LENGTH (A)	FINISH
FJ	FREEJACK	03 3"	Z ANTIQUE BRONZE
MP	MONOPOINT	06 6"	C CHROME
MO	MONORAIL	12 12"	S SATIN NICKEL
MO2	TWO-CIRCUIT MONORAIL	18 18"	
WMO	WALL MONORAIL	24 24"	

Note: MP includes 4" Round Flush Canopy.



TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500
 Tech Lighting, L.L.C.

700 ____ JON ____ ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2015 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.