Veil Pendant



DESCRIPTION

Cylindrical shade with crushed glass texture accented with inner layer of gold or silver. Includes low-voltage, 50 watt halogen bi-pin lamp or 8 watt replaceable 500 lumen 80 CRI 3000K LED SORAA® module and six feet of field-cuttable suspension cable.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

ACCESSORIES & OPTICAL CONTROLS


SORAA® LED Bi-Pin Replacement Pendant Module

WEIGHT

brown/gold



latte/gold



ORDERING INFORMATION

700 SYSTEM VEI	COLOR	FINISH	LAMP
FJ FREEJACK MP MONOPOINT MO MONORAIL MO2 TWO-CIRCUIT MONORAIL	N BROWN/GOLD L LATTE/GOLD W WHITE/SILVER	Z ANTIQUE BRONZE C CHROME S SATIN NICKEL	12 VOLT HALOGEN -LEDS830 12 VOLT LED 80 CRI 3000K -24 24 VOLT HALOGEN

Note: MP includes 4" Round Flush Canopy.Note: MP includes 4 Round Flush Canopy.

white/silver

When installing LED option on MO2 only magnetic transformers may be used.



Skokie, Illinois 60077

T 847.410.4400 F 847.410.4500

Tech Lighting, L.L.C.

700 V	EI
FIXTURE TYPE:	
JOB NAME:	
NOTES:	
-	
-	



©2015 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.