

LOW-VOLTAGE PENDANTS

Solitude Pendant

DESCRIPTION

Rectangular pressed glass shade. Includes low-voltage, 35 watt halogen bi-pin lamp or 8 watt replaceable 500 lumen 80 CRI 3000K LED SORAA® module and six feet of field-cutttable suspension cable.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

ACCESSORIES & OPTICAL CONTROLS


SORAA® LED Bi-Pin Replacement Pendant Module, Swag Hook

WEIGHT

2.5lb / 1.13kg ±



amber



amber



frost

ORDERING INFORMATION

| 700 | SYSTEM | SLD | COLOR | FINISH | LAMP |
|-----|----------------------|-----|---------|------------------|-----------------------------------|
| FJ | FREEJACK | | A AMBER | Z ANTIQUE BRONZE | 12 VOLT HALOGEN |
| MP | MONOPOINT | | F FROST | C CHROME | -LEDS830 12 VOLT LED 80 CRI 3000K |
| MO | MONORAIL | | | S SATIN NICKEL | -24 24 VOLT HALOGEN |
| MO2 | TWO-CIRCUIT MONORAIL | | | | |

Note: MP includes 4" Round Flush Canopy. Note: MP includes 4 Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.



TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500
Tech Lighting, L.L.C.

700 ____ SLD ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2015 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.