Fire Onyx Pendant



DESCRIPTION

Warm onyx in an elegant teardrop shape. Black, satin nickel, and white finish options highlighted with a satin nickel detail and clear cable; antique bronze finish includes antique bronze detail and brown cable. Includes 120 volt. 60 watt or equivalent BT15 medium base halogen lamp or GX24Q-1 base 13 watt triple tube compact fluorescent lamp (electronic ballast included). Fixture is provided with six feel of field-cuttable cable. Incandescent version dimmable with standard incandescent dimmer.

INSTALLATION

This product can mount to either a 4" square electrical box with round plaster ring or an octagon electrical box.

OTHER

TD includes 4.5" Round Canopy. Antique Bronze and Black Finish Only Available on TD. CF277 Lamp Only Available on TD.

ACCESSORIES & OPTICAL CONTROLS

Line-voltage Swag Hook

WEIGHT

4.8lb / 2.18kg ±



onyx

ORDERING INFORMATION

700 SYSTEM FIRX	COLOR	FINISH	LAMP
TD LINE-VOLTAGE PENDANTS/SUSPENSION TT SINGLE-CIRCUIT T~TRAK TT2 TWO-CIRCUIT T~TRAK	H ONYX	Z ANTIQUE BRONZE B BLACK S SATIN NICKEL W WHITE	INCANDESCENT 120V -CF COMPACT FLUORESCENT 120V -CF277 COMPACT FLUORESCENT 277V -PSUNV COMPACT FLUORESCENT PROGRAMMED START 120V-277V

onyx

For use on Halo*, Juno* or Lightolier* 120 volt single-circuit track, order as follows:

Incandescent: Order pendant as 700TD and order appropriate 120V Track Adapter


Compact Fluorescent: Substitute 700TD with one of the following: 700TH (fits Halo*), 700TJ (fits Juno*) or 700TI (fits Lightolier*) and by substituting the finish with one of the following: BZ (Black/Antique Bronze), BS (Black/Satin Nickel), WZ (White/Antique Bronze) or WS (White/Satin Nickel).

*Tech Lighting is not affiliated, nor is it endorsed by any of the companies listed nor does Tech Lighting distribute any of their products.



F 847.410.4500

Tech Lighting, L.L.C.



4.5 114 mm

4.5"

114 mm

± .5" 13 mm

1829 mm

adjustable

7.3"

185 mm

4.5"

CF MONOPOINT CANOPY

CF PROGRAMMED START

CF TT/TT2 CANOPY

7.8"

198 mm

48 mm

2.9* 74 mm

1.9"

48 mm

114 mm

145 mm

