

Tellium Head



DESCRIPTION

Simple, industrial-inspired head puts light where you need it. Machined aluminum and brass housings create crisp edges. Head rotates 360°; pivots 90° to direct the beam. Integrated lens holder accommodates up to two lenses or louvers (sold separately). Accepts low-voltage, MR16 lamp of up to 50 watts (not included).

SYSTEM

Available for FreeJack, MonoRail, and Two-Circuit MonoRail. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).


INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

ACCESSORIES & OPTICAL CONTROLS

Colored Lens, Dichroic Lens, Diffuser Lens, Eggcrate Louver, Linear Spread Lens, Soft Focus Lens, UV Filter

ORDERING INFORMATION



700	SYSTEM	TLM	LENGTH	FINISH
	FJ	FREEJACK (MONO POINT)	03 3"	Z ANTIQUE BRONZE
	MO	MONORAIL	06 6"	S SATIN NICKEL
	MO2	TWO-CIRCUIT MONORAIL	12 12"	
			18 18"	



TECH LIGHTING®

7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

www.techlighting.com

700 ____ TLM ____ ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____
