

Product Specifications - 82686MRSN				
Job Name:	Job Type:			
Quantity:	Comments			



82686MRSN

Malibu ES 1-Light Wall Sconce



Finish	Glass/Shade	Product Category
Satin Nickel	Marble	Wall Sconce

N/A Height Adjustable

Slope

Lamping		Measurements
Number of Bulbs	1	Width
Light Type	Fluorescent	Height
Bulb Type	GU24	Length
Max Bulb Wattage	13	Extension
Max Fixture Wattage	13	Back Plate Width
Rated Life	±10,000 Hours	Back Plate Height
Rated Lumens	±900	НСО
Color Temp	±2,700 K	Min Overall Height
Bulb(s) Included	Yes	Max Overall Height
Light Up/Down	N/A	Hanging Weight

81-82

N/A

N/A

	Shipping	
6.0"	Carton Weight	N/A
6.5"	Carton Width	8"
0.0"	Carton Height	6"
9"	Carton Length	8"
N/A	Carton Cubic Feet	0.20
N/A	Master Pack	1
N/A	Master Pack Weight	N/A
N/A	Master Pack Width	N/A
N/A	Master Pack Height	N/A
N/A	Master Pack Length	N/A
N/A	Master Cubic Feet	N/A
N/A	UPS Shippable	Yes

Certification		Other		Equivalents	
UL/ETL/CSA	Dry	UPC Code	783209076389	Incandescent Watts	N/A
Energy Star	Yes	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	Yes	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	Yes	Conversion Kit	N/A		
		Material	N/A		

Maxim Lighting International and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material.

Maxim Lighting International products are UL, ETL or CSA approved.

Beam Spread

Photo Cell Included

CRI

Ballast

Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.