



Product Specifications - 85812MRSN

Job Name:	Job Type:
Quantity:	Comments:



85812MRSN
Essentials ES 2-Light Bath Vanity



Finish

Satin Nickel

Glass/Shade

Marble

Product Category

Bath Vanity

Lamping

Number of Bulbs	2
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	13
Max Fixture Wattage	26
Rated Life	±10,000 Hours
Rated Lumens	±1,800
Color Temp	±2,700 K
Bulb(s) Included	Yes
Light Up/Down	Both
Beam Spread	N/A
CRI	81-82
Photo Cell Included	N/A
Ballast	N/A

Measurements

Width	18.0"
Height	7.0"
Length	0.0"
Extension	8"
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	N/A
Height Adjustable	N/A
Slope	N/A

Shipping

Carton Weight	N/A
Carton Width	8"
Carton Height	7"
Carton Length	20"
Carton Cubic Feet	0.71
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

UL/ETL/CSA	Damp
Energy Star	Yes
CA Title 24	Yes
CA Title 20	No
ADA	No

Other

UPC Code	783209081567
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	N/A

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material.

Maxim Lighting International products are UL, ETL or CSA approved.

Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.