

Lighting Your Life Since 1970

Product Specifications - 85139ICSN		
Job Name:	Job Type:	
Quantity:	Comments	



85139ICSN

Basix EE 1-Light Mini Pendant

Finish Glass/Shade **Product Category** Mini Pendant Satin Nickel

Lamping	
Number of	Bu
Light Type	

Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	13
Max Fixture Wattage	13
Rated Life	±10,000 Hours
Rated Lumens	±900
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	81-82
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	No

Measurements	
Width	6.5"
Height	
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	2.7 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	72"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

	Shipping	
.5"	Carton Weight	2.7 lbs
	Carton Width	9"
l/A	Carton Height	6"
l/A	Carton Length	14"
l/A	Carton Cubic Feet	0.41
l/A	Master Pack	1
l/A	Master Pack Weight	N/A
l/A	Master Pack Width	N/A
l/A	Master Pack Height	N/A
bs	Master Pack Length	N/A
l/A	Master Cubic Feet	N/A
l/A	UPS Shippable	Yes
l/A		
' 2"		

_			
(:6	rtific	rati	on
-		Juu	\circ

Certification		Other	
Safety Rating	Dry	UPC Code	783209059894
Energy Star	No	Shades Included	N/A
CA Title 24	Yes	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Iron

=q	uı	va	Ien	its	

Incandescent Watts	82
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.