

Lighting Your Life Since 1970

Product Specifications - 90180MRSN		
Job Name:	Job Type:	
Quantity:	Comments	



90180MRSN

Malibu 1-Light Entry Foyer Pendant

N/A

FinishGlass/ShadeProduct CategorySatin NickelMarbleEntry Foyer Pendant

Lamp	oing		
Num	ber of	Bulbs	

Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	60
Rated Life	±2,500 Hours
Rated Lumens	±672
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements	
Width	8.0"
Height	18.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	4.4 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A

	Shipping	
"	Carton Weight	4.4 lbs
"	Carton Width	12"
٩	Carton Height	8'
٩	Carton Length	14'
٩	Carton Cubic Feet	0.78
٩	Master Pack	1
٩	Master Pack Weight	N/A
٩	Master Pack Width	N/A
٩	Master Pack Height	N/A
s	Master Pack Length	N/A
٩	Master Cubic Feet	N/A
٩	UPS Shippable	Yes
"		

Certification	Other	Equivalents

Canopy Length

oo: timoution		0 11101		=quivaronto	
Safety Rating	Dry	UPC Code	783209001664	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Iron		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.