

## Lighting Your Life Since 1970

Product Specifications - 6098CLPE		
Job Name:	Job Type:	
Quantity:	Comments	



### **6098CLPE**

South Park 3-Light Outdoor Pole/Post Lantern

**Finish** Glass/Shade **Product Category** Outdoor Pole/Post Mount Pewter Clear

Number of Bulbs	3
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	40
Max Fixture Wattage	120
Rated Life	±1,500 Hours
Rated Lumens	±1,152
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

# Moseuromonte

Measurements	
Width	12.0"
Height	23.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	7.9 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	7.9 lbs
Carton Width	12"
Carton Height	22"
Carton Length	14"
Carton Cubic Feet	2.13
Master Pack	1
Master Pack Weigl	nt N/A
Master Pack Width	N/A
Master Pack Heigh	nt N/A
Master Pack Lengt	t <b>h</b> N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

### Certification Other

oor timoution		0 (1101	
Safety Rating	Wet	UPC Code	783209609860
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Solid Brass

## **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.