

Lighting Your Life Since 1970

Product Specifications - 872100I						
Job Name:	Job Type:					
Quantity:	Comments					



87210OI

Rim EE 1-Light Flush Mount

Finish Oil Rubbed Bronze		Glass/Shade White		Product Category Flush Mount	
Lamping		Measurements		Shipping	
Number of Bulbs	1	Width	13.0"	Carton Weight	2.3 lbs
Light Type	Fluorescent	Height	3.0"	Carton Width	13"
Bulb Type	4-Pin T9 Circline	Length	N/A	Carton Height	4"
Max Bulb Wattage	22	Extension	N/A	Carton Length	13"
Max Fixture Wattage	22	Back Plate Width	N/A	Carton Cubic Feet	0.43
Rated Life	±11,000 Hours	Back Plate Height	N/A	Master Pack	6
Rated Lumens	±1,050		N/A	Master Pack Weight	18.5 lbs
Color Temp	±3,000 K	Min Overall Height	N/A	Master Pack Width	13.8"
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	14.0"
Light Up/Down	N/A	Hanging Weight	2.3 lbs	Master Pack Length	26.4"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	2.94
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	No	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		
Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209048591	Incandescent Watts	95
•	No	Shades Included	N/A	Fluorescent Watts	N/A
Energy Star				Fluorescent watts	IN/A
CA Title 24	Yes	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.