

M.MARCUS LTD DUDLEY, WEST MIDLANDS DY2 0X0 Tel: 01384 457900 www.m-marcus.com

Suitable for use on 1/2 hour and 1 hour timber based fire doors when in conjunction with a fire tested lock or latch.

FD30/60

Mortice knob sets

Fitting instructions

1. Push the spindle bar into the square hole at the back of the handle.

2. Place handle onto door with the bar inserted through the square hole in the door lock/latch. Ensure handle is level and mark screw hole positions with a bradawl or an equally suitable tool, then remove handle

3. Drill pilot holes to enable screw fixing.

4. Re-align handle and spindle to the door. Measure the length of the bar that protudes through opposite side of the door. This needs to be no more than 30mm and no less than 20mm. If mpre than 30mm, than trim bar back using a hacksaw to acheive required length.

5. Second handle, repeat steps 1-3.

6. Fix both handles onto door using the wood screws provided making sure both handles are level and do not cause the door latch to stick.

Care instructions

Brass finishes: this fitting has been coated with lacquer. The use of metal polishes or abrasive cleaners will damage or discolour the surface. Regular dusting with a soft cloth, washing with warm water and a regular coating of wax polish will help keep the handle in good condition.

NOTE · In certain atmospheric conditions the lacquer finish may break down over time. The remaining traces of lacquer can be removed by the application of a paint stripper. In this case any future cleaning should be carried out by using a metal polish.

Satin chrome/polished chrome finishes: A regular application of any chrome cleaning agent will help keep the handle in good condition.

WARNINGS:

The screws enclosed with this product are brass and are liable to shear off if any sort of power tool is used to secure the door furniture with excessive pressure. When fixing onto doors, especially solid wood doors, it is advisable to drill a

pilot hole first.

Product guarantee

This product is guaranteed against manufacturing defects for a period of 10 years. Our guarantee does not cover the product where a fault occurs due to misuse, abuse, use in contravention of the instructions, or where the product has been the subject of unauthorised modifications or alterations, or has been the subject of commercial use. In the event of a problem occurring with the product within the guarantee period please return it to the store of purchase. Your statutory rights remain unaffected