

Only lighting fixtures that contain a 100% Strass crystals receive the Strass Certificate as a symbol for the best crystal stone quality. Next to diamonds and other gemstones the Strass crystal is the most suitable material for light refraction. Strass crystal components are made of the finest lead crystal with a minimum of 30% lead oxide. Strass crystal is free of impurities such as striate cords and bubbles and is therefore more lucid than air or water.



Ordering Code

Choose the desired light source, shade, finish, from the options below.

example: 220 - 209 - mc

Light Source	Shade Colors	Finish	Mounting Options
220 low voltage	209 clear	ch chrome mc matte chrome	MP4" Kiss CanopyMP22" Kiss Canopy

Technical Specs

system adaptor	Kiss 4" Mono-Point Canopy	Kiss 2" Mono-Point Canopy
220-xxx	220-xxx/MP	220-xxx/MP2
12V AC/DC input	¹ / ₂ I ^{4 1/2*} ¹ / ₂ I ¹ / ₂ ¹ / ₂ ¹ / ₂	¹ /4" ¹ /4" ¹ /4" ¹ /2" ¹ /2
50W, 5VA (max 50 Watt lamp) Dimmable	11.7V AC output 49W, 50VA (max 50 Watt lamp) Dimmable (Trailing Edge ELV)	11.7V AC output 49W, 50VA (max 50 Watt lamp) Dimmable (Trailing Edge ELV)
Connects to UNI-LIGHT system Suitable for dry locations only	Mount to 3 1/2" - 4" round J-Box Suitable for dry locations only Short circuit protection Overload protection Thermal protection	2 1/4" hole cutout Required material thickness 3/16" - 1 1/16" Suitable for dry locations only Not thru-wire rated Short circuit protection Overload protection Thermal protection