

Product Specifications for EP96075-AL						
	Job Name:	Job Type:				
	Quantity:	Comments				

N/A N/A N/A N/A

N/A 1

N/A

N/A

N/A

N/A N/A



## EP96075-AL Clipp 1-Light RapidJack Pendant

FinishGlass/ShadeProduct CategoryBrushed AluminumRapidJack Pendant

Lamping Number of Bulb(s)	1	<i>Measurements</i> Width
Light Type	Xenon	Height
Bulb Type	12V G4	Length
Max Bulb Wattage	20	Extension
Max Fixture Wattage	20	Back Plate Width
Rated Life	±2,000 Hours	Back Plate Height
Rated Lumens	±320	HCO
Color Temp	±2,900 K	Min Overall Height
Bulb(s) Included	Yes	Max Overall Height
Light Up/Down	N/A	Hanging Weight
Beam Spread	N/A	Height Adjustable
CRI	N/A	Slope
Photo Cell Included	N/A	Chain Length
Ballast/Driver/Transformer	No	Wire Length
Dimmable	Low-Voltage	Canopy Width
	-	Canopy Height

Measurements		Shipping
Width	5.00"	Carton Weight
Height	5.00"	Carton Width
Length	N/A	Carton Height
Extension	N/A	Carton Length
Back Plate Width	N/A	Carton Cubic Feet
Back Plate Height	N/A	Master Pack
HCO	N/A	Master Pack Weight
Min Overall Height	N/A	Master Pack Width
Max Overall Height	N/A	Master Pack Height
Hanging Weight	N/A	Master Pack Length
Height Adjustable	N/A	Master Cubic Feet
Slope	N/A	UPS Shippable
Chain Length	N/A	
Wire Length	120.00"	
Canopy Width	N/A	
Canopy Height	N/A	
Canopy Length	N/A	

Certification		Other			
Safety Rating	Dry	UPC Code	845094052883	Incandescent Watts	N/A
Energy Star	No	Material	N/A	Fluorescent Watts	N/A
CA Title 24	No				
CA Title 20	No				
ADA	No				

ET2 Contemporary Lighting and all designs, logos and images © 2013 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.