

This room features 6.5", 13", 13" \times 20" and 20" tiles, color 109 cream, in a modular pattern, while the multicolor border and border corner plus 6.5" tiles surround the fireplace.





Shaw Industries, Inc. PO Drawer 2128, Mail Drop 02601 Dalton, GA 30722-2128 1-800-441-7429

Piazza

Features

- Randomly screened Rotary glazing technique creates realistic and unique stone looks
- Chiseled edges created using a pneumatic needle for custom finish on each tile
- Modular design capabilities
- Designed and Crafted in Italy

Colors











100 Ivory

101 Cream

200 Gold

600 Cotto

700 Noce

Mosaic







600 Cotto





700 Noce

Accents



Border 201 Multi



Border Corner 201 Multi

Tile Sizes

Field Tile	Style
13" × 13"	CS53B
13" × 20"	CS54B
20" × 20"	CS55B
6.5" × 6.5"	CS56B

Trim

3" x 13" Bullnose CS74B

Accent

4" x 4" Border Corner	CS73B
4" x 13" Border	CS72B
13" x 13" Mosaic	CS75B

Technical

Wear Rating Group	4, 5**
Break Strength	354 lbs.
Water Absorption	<.5%
COF (Wet)	.51

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

** Color 200 and 600 PEI 4

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions...

Approved Usage







201 Multi