



Mission Bay | ceramic tile



shawfloors.com Shaw Industries, Inc. PO Drawer 2128, Mail Drop 02601 Dalton, GA 30722-2128 I -800-441 -7429

Mission Bay

Features

A red-body glazed ceramic, Mission Bay presents a visual that's refreshingly distinctive. With its chiseled edges and rustic pitting, it has the appearance of antique stone.

- $13" \times 13"$, $17" \times 17"$, $6.5" \times 6.5"$, decorative border, mosaic, bullnose
- 4 popular colors

Colors



200 Coastal Ivory



220 Seaside Beige



570 Coronado Grey



700 Cliff Point Noce

Tile Sizes

Field Tile	Style
13" × 13"	CSI3H
17" × 17"	CSI2H
6.5" × 6.5"	CSI4H
Accents	Style
3" × 13" Border	CS44H
2" × 2" Mosaic	CSI5H
Trim	Style
3" × 13" Bullnose	CSI6H
Technical Wear Rating Group Break Strength Water Absorption COF (Wet)	3 304 lbs. 6 % .55

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

