

Color shown is 200 Beige







Shaw Industries, Inc. PO Drawer 2128, Mail Drop 02601 Dalton, GA 30722-2128 1-800-441-7429

Home

Features

- Ceramic tile collection with a subtle travertine look in three neutral colors
- Features a floor/wall combo with a multi-color mosaic
- Moderate variation has a clean, contemporary look
- · Great value!

Colors







100 Bone

200 Beige

700 Café

Tile Sizes

Field Tile

13" × 13"	CS03F
17" × 17"	CS04F
10" × 13 Wall Tile	CS05F

Trim

3" x 13" Bullnose CS06F 2" x 10" Wall Bullnose CS07F

Accent

13" x 13" Mosaic CS08F Wall Listello CS29F

Technical

3*, 4 Wear Rating Group Break Strength 304/412 lbs. Water Absorption 6% COF (Wet) .48

* Color 700 is PEI 3

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions..

Approved Usage





Mosiac



101 Multi