

PRODUCT SPECIFICATIONS ■

ValueLite® Tables

November 2012

TABLE TOP

The top is composed of .070" thick, high impact polyethylene. The blow-molded top is seamless, eliminating the possibility of separation. Added UV inhibitors prevent fading and maintain appearance. The polyethylene tops are impervious to stains and easy to clean.

TABLE LEGS

Fixed height legs and frame are constructed of 19 ga. 1-1/8" tubing O.D., seam-welded tubular steel with non-marring feet (24 x 48" leg and frame are 21 ga.). Folding linkage, hinges, locks and fastening hardware are of heavy-duty die-formed steel. The gravity operated chain link leg lock puts 200% more material at the point of stress. The 24-3/4" leg stance adds strength and stability. Leg brace below the bend is stronger than common u-shaped legs.

Legs and mechanisms are furnished in a high quality, black hammertone powder coat finish.

SIZE AND WEIGHT SPECIFICATIONS

	Height	Weight	Stack Height
24 x 48"	29"	20	2-1/8"
30 x 60"	29"	35	2-1/8"
30 x 72"	29"	38	2-1/8"
30 x 72" bifold	29"	47	3-3/4"
30 x 96"	29"	47	2-1/4"
48" round	29"	34	3-5/8"
60" round	29"	53	3-5/8"
71" round	29"	73	3-5/8"
36" square	29"	47	2-1/4"

WARRANTY

10 years against defects in materials and craftsmanship.

