

Uniframe® Convertible Bench

General Information



Shown as Bench with Worksurface (UCB)



Shown as Bench with Back Support (UCB)

Features

Solid core top	•	•
High-pressure laminate surface	•	•
Bullnose edge	•	•
73P edge	•	•
Bench height 17"	•	•
Top height 27"	•	
Top height 29"	•	
Open depth 29-1/2"	•	•



Bullnose Edge



73P Edge

SPECIFICATIONS

Tops/Backs and Benches

Tops/backs and benches are of solid core 3/4" thick warp-resistant construction. Center core is 45 PCF high-density particle-board. A .030 high-pressure laminate face is used for the top surface with a .030 high-pressure laminate backer for the bottom surface. Table tops and benches are attached to the table frame with deep thread screws; expansion rivets are not to be used. Corners have a 2-1/2" radius. Tops measure 14-3/4" wide by 3/4" thick by the length of the bench.

Edges

Table top and bench edges are finished in one of the following:

A. Bullnose edge: (Flat vinyl T-edge) Edges are banded with an abrasion-resistant black vinyl bullnose molding. The barbed "T" design is inserted into a routed groove in the solid particleboard top and held in place

with nails driven from the underside, spaced approximately 8-10" apart.

B. 73P Edge: Edges are banded with a 2mm flat PVC (polyvinyl chloride) edge banding that is chemically bonded to the table or bench core.

Frames

Table frames are fabricated using a welded unitized construction, integrating all structural steel members and the ganging mechanism into a self-supporting unit. The top/back support apron is 18-gauge bent and welded steel tubing, using double tube construction for leg support vertical and leg support bottom cross tube. The main pivot folding action is heavy-duty 14-gauge steel tubing coupled with thick 11-gauge saddles. The lower leg base shall be welded to the leg assembly.

Frame Finish

Painted frame finish is non-chipping electrostatically applied and baked. Finish

is black only.

Ganging Mechanism

Steel ganging mechanism is provided on all tables as standard, allowing two tables to be locked together into a common unit. Mechanism is located on end of foot for ease of operation.

Bench Support Foot Caps

Bench support foot caps are non-marring rubber.

Casters

Large 4" diameter hard rubber swivel casters, two locking and two non-locking, provide easy and safe maneuverability.

General

Convertible benches ship knocked down in two boxes for customer assembly (unassembled). Benches are listed with Underwriters Laboratories in compliance with testing for public safety (Folding Rollaway Tables).



Uniframe[®] Convertible Bench

General Information



Shown as 2 Benches Ganged Together
(UCB-two units)



Shown as 2 Benches Nested Together
(UCB-two units)

Features

Solid core top	•	•
High-pressure laminate surface	•	•
Bullnose edge	•	•
73P edge	•	•
Folded height 33-1/4"		•
Folded depth 22"		•
Bench height 17"	•	
Top height 27"	•	
Top height 29"	•	

INFORMATION

Warranty
Refer to KI Terms & Conditions document
or visit ki.com