



FINIAL

INSTALLATION INSTRUCTIONS:

- 1. Before beginning assembly/installation, carefully unpack all parts referring to illustration for parts identification.
- 2. Turn power to installation point **OFF.** Locate the CROSSBAR and attach to ceiling mounted outlet box with (2) OUTLET BOX screws.
- 3. <u>Make the connections:</u> (Quoizel recommends (2)people for the next 2 steps). Proceed to attach HOUSE GROUND WIRE to FIXTURE GROUND WIRE. Proceed to attach both to the CROSSBAR using GROUND SCREW. Using wire connectors, connect the HOUSE WHITE WIRE to the WHITE FIXTURE SUPPLY WIRE (or RIBBED SIDE); connect the HOUSE BLACK (or RED)WIRE to the BLACK FIXTURE SUPPLY WIRE (or SMOOTH SIDE). Wrap all connections with approved electrical tape.
- 4. Carefully tuck all of the wires into the outlet box cavity and position the FIXTURE CANOPY over outlet box. Align the (2) MOUNTING SCREWS attached to CROSSBAR with the (2) MOUNTING HOLES on the underside of canopy. Pass screws through holes and secure by threading (2) LOCK BALLS onto screws. Hand tighten until snug.
- 5. Locate the NIPPLE and thread into the COUPLING on the underside of SOCKET CLUSTER. Locate the SPACER TUBE and pass over nipple. Top of tube will engage CHECK RING on underside of SOCKET CLUSTER. Locate CHECK RING and pass over nipple. Locate the RUBBER WASHER and pass over nipple. Locate the GLASS SHADE and pass mounting hole in bottom of shade over nipple. Position so the top outside edge of the GLASS SHADE rests against the inside of the DECORATIVE BALLS Pass the STEEL WASHER over nipple and secure shade by threading HEX NUT onto nipple. Tighten with pliers until snug. Pass CUP over nipple and secure by threading FINIAL onto end of nipple.
- 6. Install bulb(s) referring to fixture markings and/or labels for maximum wattage.
- 7. Restore power to installation point. Retain this sheet for replacement parts.

IF IN DOUBT ABOUT ELECTRICAL INSTALLATION, CONSULT A LICENSED ELECTRICIAN