

Incandescent Halogen


Illluma-Flex[®] Mini Pendant Trumpet Glass Low Voltage

Track

| | | Type | | | | | | | |
|-------|------|-------|------|-------|------|-------|------|-------|--|
| | -09A | -174A | -09B | -174B | -09R | -174R | -09W | -174W | |
| P6137 | | | | | | | | | |

Finish

| Catalog No. | Brushed Nickel | Urban Bronze | Glass | Lamping | Dimensions A B | | (Inches) C |
|-------------|-------------------|-----------------|-------|-------------------|-------------------|-------|---------------|
| P6137 | -09A | -174A | Amber | 12v T4 50w (Incl) | 6-3/4 | 5-1/4 | 72 |
| P6137 | -09B | -174B | Blue | 12v T4 50w (Incl) | 6-3/4 | 5-1/4 | 72 |
| P6137 | -09R | -174R | Red | 12v T4 50w (Incl) | 6-3/4 | 5-1/4 | 72 |
| P6137 | -09W | -174W | White | 12v T4 50w (Incl) | 6-3/4 | 5-1/4 | 72 |



Specifications:

General

- Flex track mini-pendant
- Trumpet shaped glass with white interior
- Plated brushed nickel (-09) or urban bronze (-174) finishes
- One 50w T4 lamp included
- Mounts anywhere along Illuma-Flex track sections, or on monopoints
- Includes adapter that allows unit to be mounted to P8516 transformer for Alpha track system also.

Mini Pendant Support

- A small wiring compartment is located just below the fitter to allow adjustment of cord length
- Cord is Teflon coated copper wire with a silicon sleeve that matches the finish

Electrical

- Attachment to 12 volt Illuma-Flex track with supplied track fitter, 120V Alpha-Track using supplied P8777 adaptor and P8516 Alpha-Track transformer or monopoint canopy (requires P8780 or P8794 accessory)
- Lamp has a GY6.35 bi-pin base

Labeling

• CSA-CSA/US listed

Progress Lighting
Post Office Box 6701
Greenville, South Carolina
29606