

SPECIFICATIONS:

DESCRIPTION

Flush-mounted round ceiling luminaires, featuring handcrafted glass. Three sizes available.

LAMPING

Standard is 60W A19 120V incandescent, suitable for dimming. **CFL:** Standard 4-Pin CFL with non-dimming electronic ballasts. **SB-CFL:** Self-ballasted GU-24 lampholders. 13W max. Consult factory for other CFL configurations. Lamps not included.

DIFFUSER

Handcrafted white glass diffuser with an attached glass ring of various decors, including distressed metallic foil applique.

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping. May be wall mounted for interior use only.


LABELS

UL or ETL Listed. Suitable for Damp Locations. Interior or Exterior Use. (Locations protected from direct precipitation)









For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.














ORDERING:



SF White/Silver Foil

Q2 2x 26W Quad 277V **V3** 3x 13W GU-24 120V





t Informati	ion:		