



PORTO

120V PENDANTS



SPECIFICATIONS:

DESCRIPTION

Cord-hung, cable-hung or stem-mount pendant with handcrafted glass diffuser.

LAMPING

Standard: 100W A19 120V incandescent, suitable for dimming, not included.

GU24 CFL: Self-ballasted GU24 lampholders. 18W max, 120V, lamp not included.

LED: 10W GU24 LED Lamp 120V, dimmable, included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 13.375" Dia. x 7.125" H

Opening sizes: 42mm top.

SUSPENSION

Cord-hung: 10' SJT-type cord. Jacket coordinates with metal finish. 5" Dia. canopy is stamped steel. Black or white powder-coat.

Cable-hung: 10' aircraft-quality stainless steel cable support with 10' AWM-type cord. Jacket coordinates with metal finish. 5" Dia. dome canopy is plated stamped steel. Bronze or Satin Nickel.

Stem-mount: 4 connectable stem sections (3", 6", 12" and 18" lengths), 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Bronze or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).

Consult factory concerning lower wattage labeling for energy requirements.



PORTO SHOWN IN SOLARE (42025L) & MOCHA (420283)



4202VM
VANILLA MATTE



420280
AMBER MATTE



420231
RED MATTE



420287
BLUE MATTE



420252
MARBLE



For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



P O R T O


ORDERING:

| CONNECTION | GLASS OPTIONS | LAMP OPTIONS | METAL FINISH | OPTIONS |
|--|--|--|--|--|
| Cable Fixture 1KX 1 Lt. Dome | 420207 White 420231 Red Matte 420252 Marble | (blank) 100W A19 Incan GU24 26W GU24 120V LED 10W LED 120V, dimmable | Cable/Stem Fixture BR Bronze SN Satin Nickel | L 15' cord LW Low wattage labeling |
| Stem Fixture 1TT 1 Lt. Flat | 420280 Amber Matte 420283 Mocha 420287 Blue Matte | | Cord Fixture BK Black (Black cord) WH White (White cord) | |
| Cord Fixture 1VC 1 Lt. Dome 1VT 1 Lt. Flat | 42025L Solare 4202VM Vanilla Matte | | | |

Ex. 1KX-4202SL-SN
Porto Pendant w/ Solare Glass,
Satin Nickel Finish


PENDANT OPTIONS:

CORD-HUNG PENDANTS




- Flat or Dome Canopy styles. Dome style allows adjustment without cutting cord.
- Suitable for sloped ceilings
- Cord: 10' SJT, 5" sleeve at socketholder
- Black or White finish

CABLE-HUNG PENDANT



- 1x 10' aircraft-quality stainless steel cable
- Suitable for sloped ceilings
- 1x lampholder
- 4-pin CFL options available
- Cord: 10' AWM-type provided
- Bronze or Satin Nickel

STEM PENDANT



- Swivel at canopy, suitable for sloped ceilings
- Includes telescoping section plus 4 connectable stem sections, (1x 3", 1x 6", 1x 12", 1x 18"), 10' max
- Bronze or Satin Nickel

LED 120V PENDANTS:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

ACCESSORIES:

ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length, up to 10' max. Telescoping adjustable section allows up to 3" movement.

- T20A-SN** or **T20A-BR** Adj. Section
- T203-SN** or **T203-BR** 3" Section
- T206-SN** or **T206-BR** 6" Section
- T212-SN** or **T212-BR** 12" Section
- T218-SN** or **T218-BR** 18" Section

Project Information: