



Product Name & Number: Belle Meade WSC28 3.25" – 32224
Collection: Lineage
Construction: Solid
Face Species: Oak (Quercus, spp USA)
Core Species: Not Applicable
Number of Plies: Not Applicable
Thickness: 3/4"
Width: 3 1/4"
Grade: #1 Common & Better
Profile: Beveled Edges/Beveled Ends
Face Finish: Smooth
Finish Treatment: Aluminum Oxide with Scotchgard Repel
Gloss Level: 60° + or - 5°
Sq. Ft. per Carton: 17.6
Sq. Ft. per Pallet: 739.2
Cartons per Pallet: 42
Weight per Carton: 49 lbs
Weight per Pallet: 2,058 lbs
Installation: Nail/Staple
On/Above Grade
Warranties: 25 year Finish on sales after August 1 2008
 15 year Finish on sales on or before July 31, 2008
Lifetime Structure
Lifetime Moisture
Janka Hardness: 1290
Photo Sensitivity: 1
Character Variation: Medium

Color Name	Color #	Quarter Round		Reducer		T-Molding		Baby Threshold		Stairnosing		Wood Filler
		HQRТА	05012	HREDF	05012	HTMDA	05012	HENDE	05012	HFSTF	05012	
Red Oak Natural	10	HQRТА	05012	HREDF	05012	HTMDA	05012	HENDE	05012	HFSTF	05012	WF-627
White Oak Natural	12	HQRТА	05058	HREDF	05058	HTMDA	05058	HENDE	05058	HFSTF	05058	WF-693
Oak Golden	20	HQRТА	05162	HREDF	05162	HTMDA	05162	HENDE	05162	HFSTF	05162	WF-639
Oak Butterscotch	22	HQRТА	05072	HREDF	05072	HTMDA	05072	HENDE	05072	HFSTF	05072	WF-693
Oak Winchester	62	HQRТА	05095	HREDF	05095	HTMDA	05095	HENDE	05095	HFSTF	05095	WF-676

PRODUCT SPEC SHEET



Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

PRODUCT SPEC SHEET