



IMPORTANT
TURN OFF THE POWER AT THE MAIN FUSE
OR CIRCUIT BREAKER BOX
BEFORE STARTING INSTALLATION

Carefully unpack and identify all parts before assembly. Bulbs are not included.

1. Thread fixture wires through center column. Install center column by screwing onto top of socket assembly.
2. Install arms:
 - A. Take one arm and hook onto top section of center column. Make certain arm is hooked onto a notch.
 - B. Then install bottom end of arm onto plate located at socket assembly by fastening with a screw from the bottom.
 - C. Repeat others. Note: make certain top and bottom section of each arm is aligned in correct angle.
3. Thread fixture wires exiting above center column through fixture loop. Install loop by screwing onto center column.
4. Install a hex nut onto one end of long threaded pipe leaving about 3/8" (10 mm) thread exposed. Screw same end of threaded pipe into bottom of socket assembly. Tighten hex nut.
5. Follow enclosed supplement installation instructions for electrical and fixture installation onto house outlet box. If you do not have an outlet box at desired location to attach the fixture than hire a qualified electrician to create one.
6. Install light bulbs (not included). See relamping label located near socket area for type and maximum allowed wattage.
7. Sit decorative pan on top of glass shade. Then while holding securely onto the glass shade, slide through the installed threaded pipe until pan touches bottom end of arms. Secure into position by fastening with a flat washer and hex nut. Afterward install finial by screwing onto protruding threaded pipe.