


IMPORTANT
TURN OFF POWER AT MAIN FUSE TO CIRCUIT
BREAKER BOX BEFORE STARTING INSTALLATION

1. Carefully unpack and identify all parts before beginning assembly. Bulb not included.
2. Remove finial by turning counter-clockwise. Then lift top cover with knob.
3. Install light bulb (not included). See relamping label at socket area for type and maximum allowed wattage.
4. Install top cover. Secure with finial.
5. Electrical installation onto post: If you are replacing and existing fixture, disconnect and remove the old fixture.
 - A) Slip lantern base over post. Mark position of holes in post cup on post.
 - B) Remove lantern base and expose the supply wiring from above post. Drill 1/8" diameter pilot holes in post at places where marked.
 - C) Make wire connections. (wire connectors not provided). Refer to chart below for correct connections. Connect fixture wires to supply wires accordingly.

Connect Black Fixture Wire to:	Connect White Fixture Wire to:
Black Supply Wire or	White Supply Wire or
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor

*Note: When parallel wire (SPT 1 & SPT2) is used. One wire is square shaped or ridged and the other wire will be round in shape or smooth. (See Illustration)



- D) Connect ground wire from supply source to fixture ground wire with connector. Never connect ground wire to black or white power supply wires. Carefully place wires inside post.
- E) Slip post cup onto post (not supplied). Align holes in post cup with holes in post. Secure them together by fastening with provided sheet metal screws.