

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF **POWER BEFORE** INSTALLING OR SERVICING THIS FIXTURE.

## Installation Steps

1. Carefully unpack your new fixture and lay out all the parts on a clear surface.
2. Thread Hex nut-2 onto the Nipple, place the Washer over the end of Nipple, thread Nipple through Mounting bar and secure with Hex nut-1 continue until tight.
3. Thread the Ground screw into the hole near the two dimples of the Mounting bar. Secure the Mounting bar to the outlet box with the Outlet box screws.
4. Weave the Fixture Wire and the Ground Wire through the Chain links-1. (Remark: Two pairs of Chain links-2 are standbys, they **can be used to** adjust the fixture's high).
5. Make Wire connections with Wire Connector:
  - The smooth wire (w/ marking) from fixture to Black Wire from power source.
  - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
  - Attach the Ground Wire and house ground wire to the Mounting bar with **the** green Ground Screw. Carefully tuck wires back into the Outlet Box.
6. Raise the Canopy onto the Nipple, and then secure with the Ball nut.
7. Place the Glass shade, Cup onto the Socket, and secure with the Socket ring.
8. Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
9. Turn on the power at fuse or Circuit Box.

