

INSTALLATION INSTRUCTIONS FOR 6182

For Wall Mount Fixture

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .

MOUNTING THE FIXTURE

- Installation (see fig.1)**
1. Shut off the power at the circuit breaker and remove old fixture, including the single bar.
 2. Thread the pipe screw part into the center hole of the single bar and secure with hex nut.
 3. Attach the single bar to the junction box using two junction box screws. The side of the single bar marked "GND" must face out.
 4. Follow wiring instructions carefully (see fig.2)
 5. Place the glass shade (A) into the frame (B).
 6. Attach the finial(D) to the bottom of the frame (B) and lock it until tight.
 7. Attach the frame (B) over the nipple, then tighten it with the ball nut (C).
 8. Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**

- Wiring (see fig.2)**
1. Connect the electrical wires as follows. Connect the black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the single bar.
 2. Tuck the wire connections neatly into the wall junction box.

