

# 93520 SPECIFICATIONS

<b>Ram Force</b>	<b>35 Ton</b>
<b>Operation</b>	Horizontal/Vertical
<b>Wedge</b>	High strength steel
<b>Cycle</b>	16 sec. (max no load)
<b>Automatic Cylinder Return</b>	Yes
<b>Hydraulic Oil System Capacity</b>	9 gal.
<b>Hydraulic Oil Type</b>	10W AW32, ASLE H-150, ISO32 or universal hydraulic fluid
<b>Hydraulic Filter</b>	External spin-on
<b>Max Log Length</b>	24 in.
<b>Max Log Weight</b>	100 lb.
<b>Log Cradle</b>	Integrated
<b>Log Catchers</b>	Included
<b>Hitch/Towing</b>	2 in. ball coupler
<b>Support Leg</b>	Adjustable
<b>Tire Size (OD)</b>	16 in.
<b>Max Towing Speed</b>	45 mph
<b>Cylinder Size (dia.)</b>	5 in.
<b>Gear Pump</b>	2 stage
<b>Max Pressure</b>	3500 psi
<b>Max Flow</b>	13 gpm
<b>Control Valve</b>	Detent (auto-return)
<b>Engine</b>	338cc Champion OHV
<b>Fuel Capacity</b>	1.64 gal.
<b>Recommended Oil Type</b>	SAE 10W-30
<b>Low Oil Shut-off</b>	Automatic
<b>Start Type</b>	Recoil
<b>Assembly</b>	Unassembled
<b>Length</b>	47.0 in.
<b>Width</b>	40.98 in.
<b>Height</b>	86.22 in.
<b>Weight</b>	562.2 lb.