

Product Information

Drop-in rim style, custom pump		K-1257-HB	shown
Fixture:*	basin area	top area	weight
Bathing well	50" (1270 mm) x 24" (610 mm)	65" (1651 mm) x 27" (686 mm)	115 lbs. (52.2 kg)
	water depth	capacity	
To overflow	14" (356 mm)	72 gal. (272.5 L)	
* Approximate measurements for comparison only.			

Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:	kw	V	Hz	A
	1.5	120	60	12.5

No change in measurements if connected with drain illustrated. (K-7166-AF or K-7166M-AF)		
Drop-in cut-out	70" (1778 mm) x 34" (864 mm)	
Minimum access panel:		
Pump/heater control	20" (508 mm) W x 15" (381 mm) H	required
Faucet area	7-1/2" (191 mm)	recommended

Required Electrical Services (2)

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 VAC, 15 A, 60 Hz
Heater	120 VAC, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump and heater.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 41 lbs./square foot (200 kg/square meter) loading.

The apron must be installed before the finish floor and wall materials are installed.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

