

Product Information

Applicable product:		5' custom bath whirlpool		K-1014-HA	
Fixture*:					
Basin area:					
Bathing well	42" (1067 mm) x 20" (508 mm)				
Top area	51" (1295 mm) x 24" (610 mm)				
Weight	110 lbs (49.8 kg)				
To overflow:					
Water depth	14" (356 mm)				
Capacity	60 gal (227 L)				
* Approximate measurements for comparison only.					
Included component:					
Cut-out template		1022451-7			
Pump:		V	Hz	A	
Variable speed		220-240	50/60	11	
Heater:	kW	V	Hz	A	
	1.5	220-240	50/60	11	

Required Electrical Service

Dedicated circuit required, protected with a Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Pump/control 220-240 V, 11 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Floor support under whirlpool must provide for a minimum of 48 lbs/square foot (233 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements with drain shown. (K-7161-AF or K-7161M-AF)

