



Catalog Information

| Model | Description | Length | Width | Height | Finishes |
|-------|--------------------------------------|----------------------------------|--------|--------|--------------|
| JT2 | 2' foot single circuit track section | 23 ³ / ₄ " | 1 3/8" | 3/4" | Black, White |
| JT4 | 4' foot single circuit track section | 47 ¹ / ₄ " | 1 3/8" | 3/4" | Black, White |
| JT6 | 6' foot single circuit track section | 71" | 1 3/8" | 3/4" | Black, White |
| JT8 | 8' foot single circuit track section | 94 ¹ / ₂ " | 1 3/8" | 3/4" | Black, White |

Product Features

- Track:** Single Circuit, 2-Wire Wide style
- Supplied:** Two end caps, & mounting hardware
- Capacity:** 20 amps rated, 120V.
- De-rating:** It is common practice to use tracks at 80% capacity to insure compatibility with dimmers, connectors, and existing wiring (1920W maximum).
- Mount:** Can be installed on drywall, or suspended ceilings.
- Cut:** Track may be cut in field.

Options / Accessories

Track may be suspended from flat, sloped ceilings. Use SK suspension kits (specify SK18, SK24, SK36, SK48, available in Black or White). For sloped ceilings, order SK14 adapter. Suspension rods may be field cut without retaping by using SK05 adapters, sold in pairs.

Material

Aluminum extrusion with copper bus wire.

Listing

UL, CUL Listed, New York City Approved

W.A.C. reserves the right to change details that do not affect overall function and performance.

