

**Catalog Information**

**2-WIRE (L)**      **3-WIRE (H)**      **WIDE 2-WIRE (J)**      **FINISHES**



LTK-703      HTK-703      JTK-703      BK, WT

Finish Key: BK-Black, WT-White

**Product Features**

- Aiming:** 90° degrees from vertical and 356° rotational.
- Compatible:** L, H, and J models in addition to fitting our own tracks are retrofitable to other manufacturers original tracks (consult factory for specific brand names).
- Special Application:** The J style head may be installed on any "J" style 2-circuit track with the addition of the J-CLIP.
- Lamping:** Re-lamps from the front.
- Socket:** Porcelain with Nickel-plated shell.

Lamp Type	Wattage	Voltage
R 30	50W – 100W	120V
A	40W – 100W	120V
PAR 30	50W – 75W	120V

**Options/Accessories**

Extensions available for "H" style 3-wire series track heads only. Available in 18", 24", 36" and 48" lengths. Specify H18, H24, H36 or H48 (in BK or WT).

**Material**

Steel with Phenolic baffle.

**Listing**

UL, CUL Listed, New York City Approved.


W.A.C. reserves the right to change details that do not affect overall function and performance.



**SPECIFICATION SHEET**

**LINE VOLTAGE TRACK HEADS**

**MODEL 703**



**Key** In Feet  
**D** Distance To Fixture From Wall Or Floor  
**FC** Initial Footcandle Level At Center Of Beam  
**L** Beam Length(where candlepower drops to 50% of maximum)  
**W** Beam Width(where candlepower drops to 50% of maximum)  
**CBCP** Center Beam Candle Power

Lamp Beam Spread	CBCP	0°Aiming Angle				30°Aiming Angle				45°Aiming Angle				60°Aiming Angle			
		D	FC	L	W	D	FC	L	W	D	FC	L	W	D	FC	L	W
50W PAR30 SP7°	13000	3'	1444	0.4'	0.4'	3'	938	0.5'	0.4'	3'	511	0.7'	0.5'	3'	181	1.5'	0.7'
		5'	520	0.6'	0.6'	5'	338	0.8'	0.7'	5'	184	1.2'	0.9'	5'	65	2.5'	1.2'
		7'	265	0.9'	0.9'	7'	172	1.1'	1.0'	7'	94	1.7'	1.2'	7'	33	3.5'	1.7'
		9'	160	1.1'	1.1'	9'	104	1.5'	1.3'	9'	57	2.2'	1.6'	9'	20	4.5'	2.2'
50W PAR30 FL25°	2000	3'	222	1.3'	1.3'	3'	144	1.8'	1.5'	3'	79	2.8'	1.9'	3'	28	6.2'	2.7'
		5'	80	2.2'	2.2'	5'	52	3.0'	2.6'	5'	28	4.7'	3.1'	5'	10	10.4'	4.4'
		7'	41	3.1'	3.1'	7'	27	4.2'	3.6'	7'	14	6.5'	4.4'	7'	5	14.6'	6.2'
		9'	25	4.0'	4.0'	9'	16	5.4'	4.6'	9'	9	8.4'	5.6'	9'	3	18.7'	8.0'
50W PAR30 FL35°	1400	3'	156	1.9'	1.9'	3'	101	2.6'	2.2'	3'	55	4.2'	2.7'	3'	19	10.8'	3.8'
		5'	56	3.2'	3.2'	5'	36	4.3'	3.6'	5'	20	7.0'	4.5'	5'	7	18.0'	6.3'
		7'	29	4.4'	4.4'	7'	19	6.1'	5.1'	7'	10	9.8'	6.2'	7'	4	25.2'	8.8'
		9'	17	5.7'	5.7'	9'	11	7.8'	6.6'	9'	6	12.6'	8.0'	9'	2	32.3'	11.4'
75W PAR30 SP10°	13000	3'	1444	0.5'	0.5'	3'	938	0.7'	0.6'	3'	511	1.1'	0.7'	3'	181	2.1'	1.0'
		5'	520	0.9'	0.9'	5'	338	1.2'	1.0'	5'	184	1.8'	1.2'	5'	65	3.6'	1.7'
		7'	265	1.2'	1.2'	7'	172	1.6'	1.4'	7'	94	2.5'	1.7'	7'	33	5.0'	2.4'
		9'	160	1.6'	1.6'	9'	104	2.1'	1.8'	9'	57	3.2'	2.2'	9'	20	6.4'	3.1'
75W PAR30 FL25°	3100	3'	344	1.3'	1.3'	3'	224	1.8'	1.5'	3'	122	2.8'	1.9'	3'	43	6.2'	2.7'
		5'	124	2.2'	2.2'	5'	81	3.0'	2.6'	5'	44	4.7'	3.1'	5'	16	10.4'	4.4'
		7'	63	3.1'	3.1'	7'	41	4.2'	3.6'	7'	22	6.5'	4.4'	7'	8	14.6'	6.2'
		9'	38	4.0'	4.0'	9'	25	5.4'	4.6'	9'	14	8.4'	5.6'	9'	5	18.7'	8.0'
75W PAR30 FL35°	2000	3'	222	1.9'	1.9'	3'	144	2.6'	2.2'	3'	79	4.2'	2.7'	3'	28	10.8'	3.8'
		5'	80	3.2'	3.2'	5'	52	4.3'	3.6'	5'	28	7.0'	4.5'	5'	10	18.0'	6.3'
		7'	41	4.4'	4.4'	7'	27	6.1'	5.1'	7'	14	9.8'	6.2'	7'	5	25.2'	8.8'
		9'	25	5.7'	5.7'	9'	16	7.8'	6.6'	9'	9	12.6'	8.0'	9'	3	32.3'	11.4'

Data based on GE PAR30 Lamps.  
 PAR30 lamps are not sold by W.A.C Lighting