

SPECIFICATIONS

Flow Rate

2.2

OPULENCE™ SINGLE HANDLE LAVATORY FAUCET

Model

D225557

Description

- · Ceramic disc valve
- 4 3/4" high spout, 6" spout length, laminar flow
- · With metal touch down drain assembly
- Single hole mount with optional deck plate DA667229
- Laminar Flow
- 1.5gpm (5.7L/min) maximum flow rate @60 psi

Standards




NSF/ANSI 372

• NSF/ANSI 372



ASME A112.18.1M/A112.18.1



Certified by IAPMO R&T



Finishes Available

- Chrome
- Other: Refer to Price List for additional finish



 ADA Accessibility Guidelines for Buildings and Facilities -309.4 Operation and Operable Parts

Warranty

Danze products are covered by a manufacturer's limited "lifetime" warranty for manufacturing defects. (153mm) 3 1/8" (80mm) 25 45° 45° **98mm** 183mm 1/2"(Min) 6 3/8" 2 3/8" (160mm) (61mm) Ø2 1/8" 🎚 (Ø54mm) 2 1/4" (55mm) 2 3/4" (68mm) 3/8 9/16"-24UNEF 3/8"Compression Ø 1 1/4" (Ø31.75mm)

Submittal Information:	
Job Name:	Location:
Contractor:	Contact #: