

**Duomo Series
HS6213**

Project _____		Fixture Type _____
Location _____		Quantity _____
Approved By _____	Date _____	Catalog Number _____

Features

Classically styled semi flush mount fixture is available with a 15 1/2" diameter and is 12 1/2" deep and is offered in two finish options. Product can be used in various applications including corridors and public spaces. Fixture mounts to standard junction box (not included).

Construction

Housing is die-formed of 22-gauge steel. Decorative ring is spun from .040" steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Back plate is finished in lighting grade white baked gloss enamel paint. Decorative spun ring is finished in plated brushed nickel or applied oil-rubbed bronze with a clear lacquer topcoat.

Diffuser

Diffuser is .200" thick molded frosted white on white swirl glass.

Electrical

This unit is wired for line voltage GU24 base sockets for 13 watt self-ballasted spring lamps; 120V/60Hz AC operation.

Lamping

GU24 base fixtures include 13 watt self-ballasted 2700K lamps. For use with 13 watt self-ballasted 2700K spring lamps included.

Certification

All fixtures are cULus listed for damp locations.

Options

- 18 or 26 watt lamping
- 120-277V HPF
- Custom finishes
- Dimming
- ENERGY STAR qualified

Specifications and dimensions subject to change without notice.

Ordering Information:

Model No.		Lamps		Dimensions	
Finish	120V	Qty	Lamp	H	DIA
Brushed Nickel	HS6213BNSCT	2	13W MAX GU24 SELF-BALLAST	12-1/2"	15-3/8"
Finish	120V	Qty	Lamp	H	DIA
Oil-Rubbed Bronze	HS6213RBSCT	2	13W MAX GU24 SELF-BALLAST	12-1/2"	15-3/8"

