



ASSEMBLY GUIDE

“Weatherly” Porch Swing

PORW1 [11.2.12]





TOOLS

- 7/16" Wrench
(Socket wrench recommended)
- Screwdriver/Square bit #1
(Power screwdriver/Square bit #1 recommended)
- Hammer

COMPONENTS

Part	Description	Qty
(A)	Swing Back	1
(B)	Swing Seat	1
(C)	Arm Rests	2
(D)	2-1/4" Carriage Bolts	10
(E)	3" Carriage Bolts	2
(F)	Open-Eye Eyebolts	2
(G)	Flange Nuts	12
(H)	Flat Washers	2
(I)	Lock Nuts	2
(J)	7' Stainless Steel Chain	2
(K)	2' Stainless Steel Chain	2
(L)	Chain Connector	2



Before you start

This assembly can be done by one person alone, however it is much easier when two people work as a team. Also, do not over-tighten bolts, but ensure that a firm and secure connection is made in every instance to avoid excess movement in joints.


STEP 1

Connect Swing Back to Swing Seat


Position and hold the Swing Back (A) and Swing Base (B) together, and attach one side using two 2-1/4" Carriage Bolts (D) and two Flange Nuts (G) as shown in Image #1 below.

Note: Holes are pre-drilled for the Carriage Bolts to pass through, but use a hammer to firmly tap the bolt end several times so that the square neck sinks into the *highwood*[®] material.

Repeat for other side.



Connect the two center braces using two 2-1/4" Carriage Bolts (D) and two Flange Nuts (G) as shown in Image #2 below.



STEP 2

Attach Arm Rests to Swing Seat and Back

With the swing resting on the swing back, position and hold Arm Rest (C) to the assembled swing and attach the front support using one Open-Eyed Eyebolt (F) and one 2-1/4" Carriage Bolt (D).


Note: Holes are pre-drilled for the Carriage Bolts to pass through, but use a hammer to firmly tap the bolt end several times so that the square neck sinks into the *highwood*[®] material.

From the inside of the swing base, attach one Flange Nut (G) to the Carriage Bolt to secure. Next, attach one Flat Washer (H) and Lock Nut (I) to the Eye Bolt making sure the Eyebolt opening faces down when fully tightened.

Finish attaching the Arm Rest to the Swing Back using one 3" Carriage Bolt (E) and one Flange Nut (G).

Both steps are shown in Image #3 below.

Repeat for other side.





STEP 3

Attaching the Swing Chains

Using the supplied 7' Stainless Steel Chain (J), attach one end to the eye bolt (F) and the other end to the pre-installed eye bolt on the swing back as shown in Image #4 below.

Attach the Chain Connector (L) to center point of the chain and to the 2' Stainless Steel Chain (K) as shown in Image #5.

Repeat on other side.



For information on Care and Cleaning your *highwood*[®] product visit www.highwood-usa.com/care.html

Visit our Website and Facebook page to see more *highwood*[®] products!

www.highwood-usa.com • www.facebook.com/highwoodUSA