Sentinel Pro TM



Anti-Scald Thermostatic/ Pressure Balanced Shower & Bath &

GENERAL SPECIFICATION

Speakman SentinelPro concealed anti-scald thermostatic/pressure balancing shower /bath valve & combinations. Chrome plated brass wall plate. Chrome plated metal lever handle. Adjustable temperature limit stop (TLS). Factory set @ 110 F°. Brass body with integral spring check stops. Dual element thermostatic/pressure balancing cartridge. Can be installed back to back. Roughing-in template. Vandal-resistant standard. S-2272-E2 showerhead with flow control device reduces flow to 2.0 gpm/7.57 lpm maximum. S-2500 shower arm and wall flange. S-1556 diverter tub spout. Four port valve with ½" female copper sweat inlets and shower outlet. ½" NPT female tub outlet. Meets ASME A112.18.1/CSA B125.1 & ASSE 1016 standards.

□ SM-5030

Anti-scald thermostatic/pressure balanced shower and bath.

OPTIONS	
SUFFIX	DESCRIPTION
□ LH	Less showerhead
1	S-2251 showerhead
□ 2	S-2252 showerhead
□ 2VR	S-2252 vandal-resistant showerhead
□ 3	S-2253 showerhead
□ 6	S-2288 showerhead
9	S-2292 showerhead



www.speakmancompany.com

Rough-Ins

SM-5030

